3M[™] Connector Covers

Circular and "D" Type Conductive Covers

3M Connector Covers are made of an intrinsically conductive composite material with uniformly distributed fibers. This makes the covers free of carbon black particulate and better suited to clean situations. The covers do not leave black marks and are permanently conductive.

3M[™] Circular Connector Covers 4270 Series


4270 Series were designed to meet the requirements and intentions of MS90376, and MIL PRF 5501/31A or 2A. Military contractors have qualified these materials to their own specifications and are encouraging their use.

3M "D" Type Connector Covers 4272 Series

4272 Series were designed to meet the requirements and intentions of MIL-PRF-5501. Military contractors have gualified these materials to their own specifications and are encouraging their use.



Specifications



Р R Ο D U С т т S н Е Е Т D Α Α

4270 and 4272 Series Connector Covers

PRODUCT CONDUCTIVE CONNECTOR COVERS

ITEM NUMBER	DATASHEET
SEE TABLE	4270

3M Electronics Solutions Division 6801 River Place Blvd Austin, TX 78726-9000 US and Canada: 866-722-3736 Fax: 866-722-3735 Intl: 919-718-0000: Fax: 919-774-8174 email: 3Mstaticinfo@mmm.com; www.3Mstatic.com 3M is a trademark of 3M Company. All other trademarks herein are the property of their respective owners.



See page 2 for sizes



Slight Attack Slight Attack

Severe Attack Severe Attack Resistant Slight Attack Dissolves

3M[™] Circular Connector Covers 4270 Series

Packaged 100/bag: 10 bags/box

Product	Α	в	С	D	
Description					
4270-4R	.670	.500	.250	.336	
4270-5R	.670	.500	.313	.399	
4270-6R	.670	.500	.375	.461	
4270-8Y	.670	.625	.413	.483	
4270-8R	.740	.500	.480	.540	
4270-9R	.750	.500	.500	.586	
4270-10Y	.750	.625	.530	.595	
4270-10R	.840	.500	.605	.665	
4270-12Y	.860	.625	.655	.715	
4270-12R	.970	.500	.720	.775	
4270-14Y	1.031	.625	.785	.845	
4270-14R	1.125	.500	.850	.905	
4270-16Y	1.125	.625	.893	.963	
4270-16R	1.220	.500	.973	1.035	
4270-18Y	1.250	.625	1.028	1.088	
4270-18R	1.330	.562	1.093	1.155	
4270-19R	1.400	.562	1.125	1.213	

Packaged 50/bag: 10 bags/box

3M

Product	Α	В	С	D	
Description					
4270-20Y	1.406	.625	1.150	1.215	
4270-20R	1.465	.562	1.231	1.301	
4270-22Y	1.500	.625	1.270	1.340	
4270-22R	1.590	.562	1.340	1.410	
4270-24Y	1.640	.625	1.390	1.460	
4270-24R	1.700	.562	1.463	1.533	
4270-25Y	1.810	.625	1.540	1.580	
4270-28Y	1.875	.625	1.645	1.718	
4270-28R	1.950	.562	1.715	1.790	

3M Logo

Mil-129H Symbol

Model Number

Packaged 25/bag: 10 bags/box

	-					
Product	Α	в	С	D		
Description						
4270-32Y	2.125	.625	1.890	1.970		
4270-32R	2.220	.562	1.965	2.040		
4270-36Y	2.340	.625	2.140	2.210		
4270-36R	2.435	.600	2.215	2.290		
4270-40Y	2.600	.625	2.380	2.450		
4270-40R	2.660	.600	2.440	2.530		
4270-44Y	2.875	.625	2.630	2.700		
4270-44R	2.960	.600	2.720	2.812		
4270-48Y	3.125	.625	2.880	2.950		
4270-48R	3.225	.600	2.960	3.050		

3M "D" Type Connector Covers 4272 Series

Packaged 100/bag: 10 bags/box


Product	Α	В	С	D	E	F	G	Н
Description								
4272-50P	2.112	2.179	2.279	.636	.536	.469	.280	.240
4272-50S	2.049	2.116	2.216	.574	.474	.407	.280	.240
4272-37P	2.216	2.283	2.383	.530	.430	.363	.280	.240
4272-37S	2.143	2.210	2.310	.462	.362	.295	.280	.240
4272-25P	1.586	1.635	1.735	.530	.430	.363	.280	.240
4272-25S	1.495	1.562	1.662	.462	.362	.295	.280	.240
4272-15P	1.040	1.107	1.177	.512	.436	.369	.280	.240
4272-15S	.955	1.022	1.122	.462	.362	.295	.280	.240
4272-9P	.708	.775	.849	.512	.434	.367	.280	.240
4272-9S	.627	.694	.794	.462	.362	.295	.280	.240


Р

R

Ο

DU





А

т

Α

D

3M Electronics Solutions Division 6801 River Place Blvd Austin, TX 78726-9000 US and Canada: 866-722-3736 Fax: 866-722-3735 Intl: 919-718-0000; Fax: 919-774-8174

Е Т

3M is a trademark of 3M Company. All other trademarks herein are the property of their respective owners.



4270 and 4272 Series Connector Covers

PRODUCT CONDUCTIVE CONNECTOR COVERS ITEM NUMBER DATASHEET 4270 SEE TABLE

т


С

н

email: 3Mstaticinfo@mmm.com; www.3Mstatic.com

Е

S



Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon,

in writing, by an authorized officer of 3M. Warranty; Limited Remedy; Limited Liability. This product will be free from defects in material and manufacture

uct, regardless of the legal theory asserted.