


Adafruit Feather 32u4 RFM95W LoRa Radio – 900MHz

PRODUCT ID: 3078



DESCRIPTION

Coming soon! Sign up to get notified when we will have these in stock.

Feather is the new development board from Adafruit, and like its namesake it is thin, light, and lets you fly! We designed Feather to be a new standard for portable microcontroller cores.

This is the Adafruit Feather 32u4 LoRa Radio (RFM95W) 900MHz – our take on an microcontroller packet radio transceiver with built in USB and battery charging. Its an Adafruit Feather 32u4 with a Long Range 900 MHz radio module cooked in! Great for making wireless networks that can go much further than 2.4GHz 802.15.4 and similar, are more flexible than Bluetooth LE and without the high power requirements of WiFi. We have other boards in the Feather family, check'em out here.

This is the 900 MHz radio version, which can be used for either 868MHz or 915MHz transmission/reception. We also sell a 433MHz version of the same radio chipset! And if you don't need LoRa radio, we have plain 900MHz packet radios as well

At the Feather 32u4's heart is an ATmega32u4 clocked at 8 MHz and at 3.3V logic, a chip setup we've had tons of experience with as it's the same as the Flora. This chip has 32K of flash and 2K of RAM, with built-in USB so not only does it have a USB-to-Serial program & debug capability built in with no need for an FTDI-like chip, it can also act like a mouse, keyboard, USB MIDI device, etc.

To make it easy to use for portable projects, we added a connector for any of our 3.7V Lithium polymer batteries and built-in battery charging. You don't need a battery, it will run just fine straight from the micro USB connector. But, if you do have a battery, you can take it on the go, then plug in the USB to recharge. The Feather will automatically switch over to USB power when it's available. We also tied the battery through a divider to an analog pin, so you can measure and monitor the battery voltage to detect when you need a recharge.

Here's some handy specs! Like all Feather 32u4's you get:

- Measures 2.0" x 0.9" x 0.28" (51 mm x 23 mm x 8 mm) without headers soldered in
- Light as a (large?) feather – 5.5 grams
- ATmega32u4 @ 8 MHz with 3.3V logic/power
- 3.3V regulator with 500mA peak current output
- USB native support, comes with USB bootloader and serial port debugging
- You also get tons of pins – 20 GPIO pins
- Hardware Serial, hardware I2C, hardware SPI support
- 8 x PWM pins
- 10 x analog inputs
- Built-in 100mA LiPo charger with charging status indicator LED
- Pin #13 red LED for general purpose blinking
- Power/enable pin
- 4 mounting holes
- Reset button

This Feather 32u4 LoRa Radio uses the extra space left over to add a RFM95W 868/915 MHz radio module:

- SX1276 based module with SPI interface
- Packet radio with ready-to-go library
- Uses the license-free ISM bands
- +13 to +20 dBm up to 100 mW Power Output Capability (selectable in software)
- Simple wire antenna or spot for uFL connector

Comes fully assembled and tested, with a USB bootloader that lets you quickly use it with the Arduino IDE. We also toss in some headers so you can solder it in and plug into a solderless breadboard. You will need to cut and solder on a small piece of wire (any solid or stranded core is fine) in order to create your antenna. Lipoly battery and USB cable not included but we do have lots of options in the shop if you'd like!

Technical Details

[FCC Test Report](#)

51mm x 23mm x 8mm / 2.0" x 0.9" x 0.28"

Weight: 5.5g