

Key **Features**

SuperClear® IPS panel technology | Frameless design | Versatile connectivity | Full HD 1080p resolution | Superior color rendering and intuitive settings



Product **Description**

The ViewSonic® VA2259-smh is a 22" (21.5" viewable) Full HD LED monitor designed for both office and home use. With SuperClear® IPS Panel technology, this monitor offers best-in-class screen performance with ultra-wide viewing angles. Vivid 1920x1080 resolution and dual speakers, combined with a sleek edge-to-edge frameless design, deliver an immersive viewing experience for home entertainment and multimedia applications. What's more, the minimalistic design of this monitor makes it perfect for nearly seamless multi-screen setups. HDMI and VGA inputs deliver flexible connectivity options for both computing and gaming environments, while ViewSonic's exclusive ViewMode feature provides intuitive presets for optimized screen performance in different applications. In addition, Flicker-Free technology and a Blue Light Filter help to minimize eyestrain from extended viewing periods. With ViewSonic's industry-leading 3-year limited warranty, this monitor is a solid long-term investment for enterprise and home applications.



22" **DISPLAY**



IPS Panel



1920 x 1080 **RESOLUTION**

Display Size (in.): 22 VESA Compatible: 100 x 100 mm		
Panel Type: IPS Resolution: 1920 x 1080 Frequency Vertical: 50~75Hz Static Contrast Ratio: 1000:1 Dynamic Contrast Ratio: 50,000,000:1 Light Source: LED Brightness: 250 cd/m2 Tilt (Forward/Back): 5° / 22° Colors: 16.7M Weight (Imperial): Response Time (Typical GTG): 14ms Net (Ibs): 6.3 Response Time (GTG w/OD): 5ms Viewing Angles: 178° horizontal, 178° vertical Gross (Ibs): 9.5 Backlight Life (Hours): 30,000 Weight (metric): Net (kg): 2.8 Compatibility: Net Without Stand (kg): 2.5 Compatibility: PC Resolution (max): Up to 1920x1080 non-interlaced Gross (kg): 4.3 Mac* Response Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1), Power in(3-pin) Physical (in.): 19.7 x 14.8 x 7.9		
Resolution: 1920 x 1080 Frequency Vertical: 50~75Hz Static Contrast Ratio: 1000:1 Dynamic Contrast Ratio: 50,000,000:1 Light Source: LED Ergonomics: Brightness: 250 cd/m2 Tilt (Forward/Back): 5° / 22° Colors: 16.7M Weight (imperial): Response Time (Typical GTG): 14ms Net (lbs): 6.3 Response Time (GTG w/OD): 5ms Net Without Stand (lbs): 5.5 Viewing Angles: 178° horizontal, 178° vertical Gross (lbs): 9.5 Backlight Life (Hours): 30,000 Weight (metric): Panel Surface: Anti-glare, hard-coating (3H) Net (kg): 2.8 Compatibility: Net Without Stand (kg): 2.5 Connector: Packaging (in.): 22.1 x 17.4 x 6.1 3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1), Power in(3-pin) Physical (in.): 19.7 x 14.8 x 7.9		
Static Contrast Ratio: 1000:1 Dynamic Contrast Ratio: 50,000,000:1 Light Source: LED Brightness: 250 cd/m2 Colors: 16.7M Response Time (Typical GTG): 14ms Response Time (GTG w/OD): 5ms Viewing Angles: 178° horizontal, 178° vertical Backlight Life (Hours): 30,000 Panel Surface: Anti-glare, hard-coating (3H) Compatibility: PC Resolution (max): Up to 1920x1080 Mac* Resolution (max): Up to 1920x1080 Connector: Packaging (in.): 22.1 x 17.4 x 6.1 Physical (in.): 19.7 x 14.8 x 7.9		
Dynamic Contrast Ratio: 50,000,000:1 Light Source: LED Brightness: 250 cd/m2 Colors: 16.7M Response Time (Typical GTG): 14ms Response Time (GTG w/OD): 5ms Viewing Angles: 178° horizontal, 178° vertical Backlight Life (Hours): 30,000 Panel Surface: Anti-glare, hard-coating (3H) Compatibility: PC Resolution (max): Up to 1920x1080 Mac* Resolution (max): Up to 1920x1080 Connector: 3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1), Power in(3-pin) Physical (in.): Separate Sync, Con Sync on Green, TM Separate Sync, Con Sync on Green, TM Separate Sync, Con Sync on Green, TM Ergonomics: Tilt (Forward/Back): 5° / 22° Weight (imperial): 6.3 Net (lbs): 5.5 Net Without Stand (lbs): 5.5 Net (kg): 2.8 Compatibility: 2.5 Connector: 22.1 x 17.4 x 6.1		
Light Source: Brightness: 250 cd/m2 Tilt (Forward/Back): Weight (imperial): Response Time (Typical GTG): Viewing Angles: 178° horizontal, 178° vertical Backlight Life (Hours): Panel Surface: Anti-glare, hard-coating (3H) Met (kg): PC Resolution (max): PC Resolution (max): Up to 1920x1080 non-interlaced Mac* Resolution (max): Up to 1920x1080 Dimensions (imperial) (WxHxD): Physical (in.): Sync on Green, TM Sync on Green, TM Ergonomics: Tilt (Forward/Back): 5° / 22° Weight (imperial): Net (lbs): 6.3 Net Without Stand (lbs): 5.5 Weight (metric): Net (kg): 2.8 Compatibility: PC Resolution (max): Up to 1920x1080 non-interlaced Dimensions (imperial) (WxHxD): Packaging (in.): 22.1 x 17.4 x 6.1		
Brightness: 250 cd/m2 Tilt (Forward/Back): 5° / 22° Colors: 16.7M Weight (imperial): Response Time (Typical GTG): 14ms Net (lbs): 6.3 Response Time (GTG w/OD): 5ms Net Without Stand (lbs): 5.5 Viewing Angles: 178° horizontal, 178° vertical Gross (lbs): 9.5 Backlight Life (Hours): 30,000 Weight (metric): Panel Surface: Anti-glare, hard-coating (3H) Net (kg): 2.8 Compatibility: Net Without Stand (kg): 2.5 PC Resolution (max): Up to 1920x1080 non-interlaced Gross (kg): 4.3 Mac* Resolution (max): Up to 1920x1080 Dimensions (imperial) (WxHxD): Connector: Packaging (in.): 22.1 x 17.4 x 6.1 3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1), Power in(3-pin) Physical (in.): 19.7 x 14.8 x 7.9		
Colors: 16.7M Weight (imperial): Response Time (Typical GTG): 14ms Net (lbs): 6.3 Response Time (GTG w/OD): 5ms Net Without Stand (lbs): 5.5 Viewing Angles: 178° horizontal, 178° vertical Gross (lbs): 9.5 Backlight Life (Hours): 30,000 Weight (metric): Panel Surface: Anti-glare, hard-coating (3H) Net (kg): 2.8 Compatibility: Net Without Stand (kg): 2.5 PC Resolution (max): Up to 1920x1080 non-interlaced Gross (kg): 4.3 Mac® Resolution (max): Up to 1920x1080 Dimensions (imperial) (WxHxD): Connector: Packaging (in.): 22.1 x 17.4 x 6.1 3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1), Power in(3-pin Physical (in.): 19.7 x 14.8 x 7.9		
Response Time (Typical GTG): 14ms Net (Ibs): 6.3 Response Time (GTG w/OD): 5ms Net Without Stand (Ibs): 5.5 Viewing Angles: 178° horizontal, 178° vertical Gross (Ibs): 9.5 Backlight Life (Hours): 30,000 Panel Surface: Anti-glare, hard-coating (3H) Compatibility: Net Without Stand (kg): 2.8 PC Resolution (max): Up to 1920x1080 non-interlaced Gross (kg): 4.3 Mac* Resolution (max): Up to 1920x1080 Dimensions (imperial) (WxHxD): Connector: Packaging (in.): 22.1 x 17.4 x 6.1 3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1), Power in(3-pin Physical (in.): 19.7 x 14.8 x 7.9		
Response Time (GTG w/OD): 5ms Net Without Stand (lbs): 5.5 Viewing Angles: 178° horizontal, 178° vertical Gross (lbs): 9.5 Backlight Life (Hours): 30,000 Panel Surface: Anti-glare, hard-coating (3H) Compatibility: Net Without Stand (kg): 2.5 PC Resolution (max): Up to 1920x1080 non-interlaced Gross (kg): 4.3 Mac° Resolution (max): Up to 1920x1080 Dimensions (imperial) (WxHxD): Connector: Packaging (in.): 22.1 x 17.4 x 6.1 3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1), Power in(3-pin Physical (in.): 19.7 x 14.8 x 7.9		
Viewing Angles: 178° horizontal, 178° vertical Gross (lbs): 9.5 Backlight Life (Hours): 30,000 Panel Surface: Anti-glare, hard-coating (3H) Compatibility: Net Without Stand (kg): 2.5 PC Resolution (max): Up to 1920x1080 non-interlaced Gross (kg): 4.3 Mac® Resolution (max): Up to 1920x1080 Dimensions (imperial) (WxHxD): Connector: Packaging (in.): 22.1 x 17.4 x 6.1 3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1), Power in(3-pin Physical (in.): 19.7 x 14.8 x 7.9		
Backlight Life (Hours): 30,000 Panel Surface: Anti-glare, hard-coating (3H) Compatibility: Net Without Stand (kg): 2.5 PC Resolution (max): Up to 1920x1080 non-interlaced Gross (kg): 4.3 Mac* Resolution (max): Up to 1920x1080 Dimensions (imperial) (WxHxD): Connector: Packaging (in.): 22.1 x 17.4 x 6.1 3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1), Power in(3-pin Physical (in.): 19.7 x 14.8 x 7.9		
Panel Surface: Anti-glare, hard-coating (3H) Net (kg): 2.8 Compatibility: PC Resolution (max): Up to 1920x1080 non-interlaced Gross (kg): Anti-glare, hard-coating (3H) Net (kg): 2.5 Anti-glare, hard-coating (3H) Net (kg): 2.5 Gross (kg): 4.3 Dimensions (imperial) (WxHxD): Connector: Packaging (in.): 22.1 x 17.4 x 6.1 3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1), Power in(3-pin) Physical (in.): 19.7 x 14.8 x 7.9		
Compatibility: PC Resolution (max): Up to 1920x1080 non-interlaced Mac* Resolution (max): Up to 1920x1080 Dimensions (imperial) (WxHxD): Connector: Packaging (in.): 2.5 4.3 Dimensions (imperial) (WxHxD): Packaging (in.): 19.7 x 14.8 x 7.9		
PC Resolution (max): Up to 1920x1080 non-interlaced Gross (kg): 4.3 Mac* Resolution (max): Up to 1920x1080 Dimensions (imperial) (WxHxD): Connector: Packaging (in.): 22.1 x 17.4 x 6.1 3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1), Power in(3-pin Physical (in.): 19.7 x 14.8 x 7.9		
Mac® Resolution (max): Up to 1920x1080 Dimensions (imperial) (WxHxD): Connector: Packaging (in.): 22.1 x 17.4 x 6.1 3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1), Power in(3-pin Physical (in.): 19.7 x 14.8 x 7.9		
Connector: Packaging (in.): 22.1 x 17.4 x 6.1 3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1), Power in(3-pin Physical (in.): 19.7 x 14.8 x 7.9		
3.5mm Audio In(1), 3.5mm Audio Out(1), HDMI(1), VGA(1), Power in(3-pin Physical (in.): 19.7 x 14.8 x 7.9		
Physical Without Stand (in.): 19.7 x 11.9 x 1.8		
Audio: Internal Speakers: 2-watt (x2) Dimensions (metric) (WxHxD):		
Packaging (mm): 562 x 443 x 155		
Eco Mode (Conserve): 16W Physical (mm): 499.7 x 375.1 x 200)	
Eco Mode (optimized): 20W Physical Without Stand (mm): 499.7 x 301.9 x 45.5	5	
Consumption (typical): 25W General:		
Regulations: CE EMC, CB, RoHS Green BOM & RoHS DoC, RI		
Consumption (max): 27W and DoC, ErP, WEEE, US NRTL w/ CA, FCC-B w/ ICES003, EN EPEAT Silver, Mexico CoC, Mexico Energy		
Voltage: AC 100-240V (universal), 50-60Hz PACKAGE CONTENTS: VA2259-smh monitor, Power cable, A	Audio cable, VGA	
Additional Hardware: cable, Quick Start Guide, ViewSonic Wizard CD		
Kensington Lock Slot: 1 Recycle/Disposal: Please dispose of in accordance with loc federal laws.	cal, state or	
Physical Controls: 1, 2, Down, Up, Power Warranty: Three-year limited warranty on parts, labor and	backlight	
Auto Image Adjust, UPC: 766907836530		
Contrast/Brightness, Input Select,		
On Screen Display: Information, Manual Image Adjust,		
Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) Awards: Awards:		
Operating Conditions:		
Temperature: 32-104° F (0-40° C)		

Copyright © ViewSonic Corporation 2000-2017. All rights reserved. (08/16/2017 05:56 PM PST)

20-90%

Humidity (non-condensing):