ACP-2000/ IPC-602

2U 6-Slot Rackmount Chassis with Front USB and PS/2 Interfaces



Features

- 2U rackmount chassis supports up to 6 cards
- Butterfly backplane design
- Front-accessible USB and PS/2 connectors
- 250W / 300W AC ATX and DC power supply options
- Two 40 CFM cooling fans with air filter
- Lockable front door prevents unauthorized access
- System alarm notification by front LED indicators (ACP-2000 only)

Specifications

		Front-accessible	Internal	
Drive Bay	Slim Optical Disk Drive	1/-	-	
DIIVE Day	3.5"	2/1	-/1	
	5.25"	-/1	-	
Cooling	Fan	2 (8 cm / 47 CFM each) / 2 (8 cm / 40 CFM eac	h)	
Cooling	Air Filter	Yes		
Front I/O Interface	USB	2		
FIOIILI/O IIILEIIACE	PS/2	1		
Missellansous	LED Indicators	Power and HDD activity; fan and temperature for ACP-2000 only		
Miscellaneous	Rear Panel	One 9-pin D-Sub opening		
		Operating	Non-Operating	
	Temperature	0 ~ 40° C (32 ~ 104° F)	-20 ~ 60° C (-4 ~ 140° F)	
Environment	Humidity	10 ~ 85% @ 40° C, non-condensing	10 ~ 95% @ 40° C, non-condensing	
	Vibration (5 ~ 500 Hz)	0.5 Grms	2 G	
	Shock	10 G (with 11 ms duration, half sine wave)	30 G	
Dhusiaal Characteristics	Dimensions (W x H x D)	482 x 88 x 451 mm (19" x 3.5" x 17.8")		
Physical Characteristics	Weight	11.5 kg (25.3 lb) / 11.3 kg (24.9 lb)		

Inside View


Front View

IPC-602



ADVANTECH Industrial Computer Chassis
All product specifications are subject to change without notice

ACP-2000/IPC-602



Ordering Information

Part Number	Power Supply	Backplane
PICMG 1.0		
ACP-2000P3-00XE	Without power supply, with ATX switch	989K610622E (PCA-6106P3V)
ACP-2000P4-00XE	Without power supply, with ATX switch	989K610512E (PCA-6105P4V)
IPC-602P3-00XBE	Without power supply, with ATX switch	989K610622E (PCA-6106P3V)
IPC-602P4-00XBE	Without power supply, with ATX switch	989K610512E (PCA-6105P4V)
PICMG 1.3		
ACP-2000EBP-00XE	Without power supply, with ATX switch	-
IPC-602FBP-00XBF	Without power supply with ATX switch	-

Power Supply Options

(For detailed power supply specs, please refer to Chapter 13)

Part Number		Specifications		
Fall Nulliver	Watts	Input		
	PS8-250ATX-ZE (ATX, PFC) (IPC-602 only)	250W	AC 100 ~ 240 V (full range)	
	PS8-300ATX-ZBE (ATX, PFC)	300W	AC 100 ~ 240 V (full range)	
	PS8-400ATX-ZE (ATX, PFC)	400W	AC 100 ~ 240 V (full range)	
	PS-300ATX-DC48E (ATX)	300W	DC -48 V	
	RPS-300ATX-ZE (ATX, PFC) (1+1 redundant.ACP-2000 only)	300W	AC 100 ~ 240 V (full range)	

Optional Accessories

Part Number	Description
1950000868T00B	P3 and X3 card cage
1950000869N002	P4 card cage
96CB-SATAPOWER-6P1	SATA power wire 6-pin to big 4-pin (for slim ODD)
IDT-3120E	Mobile rack for converting a 3.5" drive bay to dual 2.5" SATA HDD trays

Spare Parts

Part Number	Description
2130006189S000	Door filter 156 x 45 x 5 mm
1990001949	Fan filter 165 x 58 mm