




### General Description

The AO6704/L uses advanced trench technology to provide excellent  $R_{DS(ON)}$  and low gate charge. A Schottky diode is provided to facilitate the implementation of a bidirectional blocking switch, or for DC-DC conversion applications.

### Product Summary

$V_{DS}$  (V) = 30V  
 $I_D = 3.6A$  ( $V_{GS} = 10V$ )  
 $R_{DS(ON)} < 65m\Omega$  ( $V_{GS} = 10V$ )  
 $R_{DS(ON)} < 75m\Omega$  ( $V_{GS} = 4.5V$ )  
 $R_{DS(ON)} < 160m\Omega$  ( $V_{GS} = 2.5V$ )  
**SCHOTTKY**  
 $V_{DS}$  (V) = 20V  
 $I_F = 1A$   
 $V_F < 0.5V @ 0.5A$



### Absolute Maximum Ratings $T_A=25^\circ\text{C}$ unless otherwise noted

Parameter	Symbol	MOSFET	Schottky	Units
Drain-Source Voltage	$V_{DS}$	30		V
Gate-Source Voltage	$V_{GS}$	$\pm 12$		V
Continuous Drain Current <sup>A</sup>	$I_D$	$T_A=25^\circ\text{C}$	3.6	A
		$T_A=70^\circ\text{C}$	2.9	
Pulsed Drain Current <sup>B</sup>	$I_{DM}$	10		
Schottky reverse voltage	$V_{KA}$		20	V
Continuous Forward Current <sup>A</sup>	$I_F$	$T_A=25^\circ\text{C}$	1.5	A
		$T_A=70^\circ\text{C}$	1	
Pulsed Forward Current <sup>B</sup>	$I_{FM}$		10	
Power Dissipation	$P_D$	$T_A=25^\circ\text{C}$	1.39	W
		$T_A=70^\circ\text{C}$	0.89	
Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 to 150	-55 to 150	$^\circ\text{C}$

Parameter: Thermal Characteristics MOSFET	Symbol	Typ	Max	Units
Maximum Junction-to-Ambient <sup>A</sup>	$R_{\theta JA}$	70	90	$^\circ\text{C/W}$
Maximum Junction-to-Ambient <sup>A</sup>				
Maximum Junction-to-Lead <sup>C</sup>	$R_{\theta JL}$	51	80	
Thermal Characteristics Schottky				
Maximum Junction-to-Ambient <sup>A</sup>	$R_{\theta JA}$	129	160	$^\circ\text{C/W}$
Maximum Junction-to-Ambient <sup>A</sup>				
Maximum Junction-to-Lead <sup>C</sup>	$R_{\theta JL}$	52	80	

Electrical Characteristics ( $T_J=25^\circ\text{C}$  unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
<b>STATIC PARAMETERS</b>						
$BV_{DSS}$	Drain-Source Breakdown Voltage	$I_D=250\mu\text{A}$ , $V_{GS}=0\text{V}$	30			V
$I_{DSS}$	Zero Gate Voltage Drain Current	$V_{DS}=24\text{V}$ , $V_{GS}=0\text{V}$ $T_J=55^\circ\text{C}$			1 5	$\mu\text{A}$
$I_{GSS}$	Gate-Body leakage current	$V_{DS}=0\text{V}$ , $V_{GS}=\pm 12\text{V}$			100	nA
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}$ , $I_D=250\mu\text{A}$	1	1.4	1.8	V
$I_{D(ON)}$	On state drain current	$V_{GS}=4.5\text{V}$ , $V_{DS}=5\text{V}$	10			A
$R_{DS(ON)}$	Static Drain-Source On-Resistance	$V_{GS}=10\text{V}$ , $I_D=3.6\text{A}$ $T_J=125^\circ\text{C}$		44 64	65 90	$\text{m}\Omega$
		$V_{GS}=4.5\text{V}$ , $I_D=3.4\text{A}$		53	75	$\text{m}\Omega$
		$V_{GS}=2.5\text{V}$ , $I_D=1\text{A}$		106	160	$\text{m}\Omega$
$g_{FS}$	Forward Transconductance	$V_{DS}=5\text{V}$ , $I_D=3.6\text{A}$		11.7		S
$V_{SD}$	Diode Forward Voltage	$I_S=1\text{A}$ , $V_{GS}=0\text{V}$		0.81	1	V
$I_S$	Maximum Body-Diode Continuous Current				2.5	A
<b>DYNAMIC PARAMETERS</b>						
$C_{iss}$	Input Capacitance	$V_{GS}=0\text{V}$ , $V_{DS}=15\text{V}$ , $f=1\text{MHz}$		226	270	pF
$C_{oss}$	Output Capacitance			39		pF
$C_{rss}$	Reverse Transfer Capacitance			29		pF
$R_g$	Gate resistance	$V_{GS}=0\text{V}$ , $V_{DS}=0\text{V}$ , $f=1\text{MHz}$		1.4	4	$\Omega$
<b>SWITCHING PARAMETERS</b>						
$Q_g$	Total Gate Charge	$V_{GS}=4.5\text{V}$ , $V_{DS}=15\text{V}$ , $I_D=3.6\text{A}$		3	3.6	nC
$Q_{gs}$	Gate Source Charge			1.4		nC
$Q_{gd}$	Gate Drain Charge			0.55		nC
$t_{D(on)}$	Turn-On Delay Time	$V_{GS}=10\text{V}$ , $V_{DS}=15\text{V}$ , $R_L=3.9\Omega$ , $R_{GEN}=6\Omega$		2.6		ns
$t_r$	Turn-On Rise Time			3.2		ns
$t_{D(off)}$	Turn-Off Delay Time			14.5		ns
$t_f$	Turn-Off Fall Time			2.1		ns
$t_{rr}$	Body Diode Reverse Recovery Time	$I_F=3.6\text{A}$ , $dI/dt=100\text{A}/\mu\text{s}$		10.2	13	ns
$Q_{rr}$	Body Diode Reverse Recovery Charge	$I_F=3.6\text{A}$ , $dI/dt=100\text{A}/\mu\text{s}$		3.8		nC
<b>SCHOTTKY PARAMETERS</b>						
$V_F$	Forward Voltage Drop	$I_F=0.5\text{A}$		0.39	0.5	V
$I_{rm}$	Maximum reverse leakage current	$V_R=16\text{V}$			0.1	mA
		$V_R=16\text{V}$ , $T_J=125^\circ\text{C}$			20	
$C_T$	Junction Capacitance	$V_R=10\text{V}$		34		pF
$t_{rr}$	Schottky Reverse Recovery Time	$I_F=1\text{A}$ , $dI/dt=100\text{A}/\mu\text{s}$		5.2	10	ns
$Q_{rr}$	Schottky Reverse Recovery Charge	$I_F=1\text{A}$ , $dI/dt=100\text{A}/\mu\text{s}$		0.8		nC

A: The value of  $R_{\theta JA}$  is measured with the device mounted on 1 in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with  $T_A=25^\circ\text{C}$ . The value in any a given application depends on the user's specific board design. The current rating is based on the  $t \leq 10\text{s}$  thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C: The  $R_{\theta JA}$  is the sum of the thermal impedance from junction to lead  $R_{\theta JL}$  and lead to ambient.

D: The static characteristics in Figures 1 to 6 are obtained using 80  $\mu\text{s}$  pulses, duty cycle 0.5% max.

E: These tests are performed with the device mounted on 1 in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with  $T_A=25^\circ\text{C}$ . The SOA curve provides a single pulse rating.

Rev 4: Nov. 2010

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance