

Customer Specification PART NO. M244804

Construction

				Diameters (In)		
1) Component 1		6 X 1 COND	6 X 1 COND			
a) Conductor		22 (7/30) AWG	22 (7/30) AWG BC		0.030	
b) Insulation		0.010" Wall, No	0.010" Wall, Nom. PVC, Plenum Rated		0.050	
(1) Color(s)						
Cond	Color	Cond	Color	Cond	Color	
1	BLACK	3	WHITE	5	BROWN	
2	RED	4	GREEN	6	BLUE	
2) Cable Assembly		6 Components	6 Components Cabled			
a) Twists:		5.3 Twists/foot	5.3 Twists/foot (min)			
3) Shield:		Alum/Mylar Tap	Alum/Mylar Tape, 25% Overlap, Min.			
a) Foil Direction		Foil Facing Out	Foil Facing Out			
b) Drain Wire		24 (7/32) AWG	24 (7/32) AWG TC			
4) Jacket		0.015" Wall, No	0.015" Wall, Nom.,PVC, Plenum Rated		0.185 (0.195 Max.)	
a) Color(s)		WHITE	WHITE			
b) Print		EXXXXXX 75C * = Factory Cod	ALPHA WIRE-* P/N M244804 6C 22 AWG EXXXXX 75C CMP (UL) C(UL) ROHS * = Factory Code [Note: Product may have c(UL) or CSA markings depending upon plant of manufacture.]			

Applicable Specifications

1) UL	СМР	75°C
2) CSA International	C(UL) TYPE CMP	75°C
	FT6	

Environmental

1) EU Directive 2002/95/EC(RoHS):		
	All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for compliance Date of Manufacture.	

Properties

Physical & Mechanical Properties		
1) Temperature Range	-20 to 75°C	
2) Bend Radius	10X Cable Diameter	
3) Pull Tension	37 Lbs, Maximum	
Electrical Properties	(For Engineering purposes only)	
1) Voltage Rating	^{300 V} RMS	
2) Capacitance	46 pf/ft @1 kHz, Nominal Conductor to Conductor	
3) Ground Capacitance	83 pf/ft @1 kHz, Nominal	
4) Inductance	0.18 μH/ft, Nominal	
5) Conductor DCR	15.2 Ω/1000ft @20°C, Nominal	
6) OA Shield DCR	15.9 Ω/1000ft @20°C, Nominal	

Other

Packaging	Flange x Traverse x Barrel (inches)
a) 1000 FT	12 x 6 x 3.5 Continuous length
b) 500 FT	12 x 4.5 x 3.5 Continuous length
c) 100 FT	6.5 x 2 x 1.9 Continuous length
d) Bulk(Made-to-order)	
	[Spool dimensions may vary slightly]

www.alphawire.com

Alpha Wire | 711 Lidgerwood Avenue, Elizabeth, NJ 07207 Tel: 1-800-52 ALPHA (25742)

Although Alpha Wire ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha had been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

ALPHA WIRE - CONFIDENTIAL AND PROPRIETARY

Notice to persons receiving this document and/or technical information. This document is confidential and is the exclusive property of ALPHA WIRE, and is merely on loan and subject to recall by ALPHA WIRE at any time. By taking possession of this document, the recipient acknowledges and agrees that this document cannot be used in any manner adverse to the interests of ALPHA WIRE, and that no portion of this document may be copied or otherwise reproduced without the prior written consent of ALPHA WIRE. In the case of conflicting contractual provisions, this notice shall govern the status of this document. ©2013 ALPHA WIRE - all rights reserved.