

Item # 19210-11, 16 Amps Rotary Red Handle SD1 Series DIN Rail Mounted Disconnect Switch

16 - 40 Amps

Allows breaking and disconnecting on load of equipment on low voltage at nominal current.



[SPECIFICATIONS](#) · [OPTIONS](#) · [CERTIFICATIONS](#)

SPECIFICATIONS

Handle Color	Red
Rated Current	16 A
Maximum Voltage	600 V
Short Circuit Rating	5 kA
Maximum UL Horsepower 3-Phase (120 V)	3 hp
Wire Range	16 - 6 AWG
Tightening Torque	2 N·m

OPTIONS

Options	19400-11, Black Handle Door Interlock (\$8.35) 19401-11, Red/Yellow Handle Emergency Door Interlock (\$8.35) 19414, SD1 Series 4th Pole (\$12.50) 19419, SD1 Series Neutral Pole (\$15.63) 19421, SD1 Series Ground Pole (\$15.63) 19423, SD1 Series Aux Contact SPST (\$15.63) 19440, 6 - 8 Pole Connector (\$14.92) 19535-100, 100 mm Length Remote Operator Shaft (\$4.16) 19535-200, 200 mm Length Remote Operator Shaft (\$5.22) 19535-300, 300 mm Length Remote Operator Shaft (\$6.26)
---------	--

CERTIFICATIONS

Certifications	 RoHS (EU directive 2002/95/EC)
----------------	---