

TOP VIEW




LABEL:

MADE BY AMGIS LLC USA
 INDUCTOR P/N IND-10565A
 L= 1.2 mH I= 7.2A
 DATE CODE-S/N

RELEASE HISTORY			
REL.	DESCRIPTION	DATE	APPROVED
000	INITIAL RELEASE	06/05/2014	JJ

SCHEMATIC



WIND BACK & FORTH IN 5 LAYERS.


NOTES:

1. HEADER: LODESTONE PACIFIC VTM254-4 (WITH 4 PINS #16 AWG)
2. CORE MICROMETALS T200-8/90
3. MAGNET WIRE 16 HPTZ.
4. EPOXY JB WELD OR APPROVED EQUIVALENT.
5. SOLDER SN96

ELECTRICAL

1. INDUCTANCE @ 250 mV, 15 KHz:
(1-2)= 1.8 mH ± 10%
2. DCR:
(1-2)= 175mΩ REF



 AMGIS LLC, INC PROPRIETARY AND CONFIDENTIAL THIS DRAWING IS THE PROPERTY OF AMGIS LLC, INC. IT IS LOANED WITH THE UNDERSTANDING THAT IT MAY NOT BE REPRODUCED NOR MAY THE INFORMATION CONTAINED HEREIN BE USED FOR MANUFACTURING PURPOSES WITHOUT WRITTEN CONSENT FROM AMGIS LLC, INC.	NAME	DATE	TITLE:	
	DRAWN	DF	06/05/2014	INDUCTOR
	APPROVED	JJ	06/05/2014	
	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			
TOLERANCES:		DWG. NO		
FRACTIONS: ± 1/64		IND-10565A		
ONE PLACE DECIMAL: ± .050		REL		000
TWO PLACE DECIMAL: ± .010		SCALE: NONE		
THREE PLACE DECIMAL: ± .005		WEIGHT: .6 LBS		SHEET 1 OF 1
DO NOT SCALE DRAWING				