




PRODUCT NO	FINISH ぬ.こ
66971-102	SEE NOTE 注4参照 PLATING A
66971-202	ぬ.こ B PLATING B

REVISIONS			
REV	DESCRIPTION	BY	DATE
0	REV	T.P.	5/1/77
A	REVISED	Om	4/1/78



SECTION B-B



SECTION A-A

NOTE:

1. CONTACT WITHDRAWAL FORCE TO BE 30GR. MIN. WHEN MATED WITH Q.61 SQ. STEEL GAGE PIN.
2. MATING HEADER: Q.64 ± 0.03 SQ. OR ROUND PIN
3. HOUSING MATL: 15% GLASS FIBER FILLED PBT RESIN RATED PER UL 94V0
COLOR: BLUE
4. CONTACT MATL: .02 THK. PHOSPHOR BRONZE
PLATING A; CONTACT AREA .05mm MIN GOLD OVER 1.3mm NICKEL.
PLATING B; CONTACT AREA .05mm MIN GOLD OVER 1.3mm NICKEL OTHER GOLD FLASH OVER 1.3mm NICKEL.

注:

1. コンタクト引抜き力は最小 30gr. (Q.61 角スチールゲージピン使用)
2. 適合する相手ヘッダーは Q.64 ± 0.03 角又は丸ピン
3. ハウジング材料: 15% ガラス繊維入り PBT 樹脂 規格 UL 94-V0, 色 紺青
4. コンタクト材料: .02mm 厚リン青銅.
ぬ.こ A; コンタクト接触部は 1.3mm ニッケルめっき
に最小 0.5mm の金めっき. 他の部分に 1.3mm ニッケルめっき
ぬ.こ B; コンタクト接触部は 1.3mm ニッケルめっき
に最小 0.5mm の金めっき. 他の部分に 1.3mm ニッケルめっき
に全 フラッシュ.

THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN BERG PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM BERG ELECTRONICS.
DO NOT SCALE PRINT

CUSTOMER COPY
FOR REFERENCE ONLY

DO NOT SCALE DRAWING		TOLERANCES UNLESS OTHERWISE NOTED	INCH	MM	DR	MATL	DATE
		LINEAR	0.01	0.00 ± 0.2	9.8	SEE NOTE	5/1/77
			0.001	0.00 ± 0.1	OK'D		4/1/77
THIRD ANGLE PROJECTION					ENGR	FINISH	5/1/77
APPLICATION		ANGLES			APP'D		

BERG
ELECTRONICS

TITLE 10MM H 2POS. JUMPER CONNECTOR		
SCALE	SIZE	DWG. NO.
5-1	B	66971

SHEET 1 OF 1

NOTE: This print is the property of and embodies proprietary designs of Berg Electronics. No part of this drawing or any other part of this drawing shall be used or reproduced without the written consent of Berg Electronics.