



**Material:**

- Cable: UL2725 [26AWG(1/0.404)\*2+D(1/0.32)\*2+AL]\*2F  
- OD 2.2\*7.8MM  
- Jacket Red (200C/RD-16#)
- P1/P3 Connector: eSATA 7P/M Solder Type  
- Pin G/F  
- Insulator Black Metal  
- Shell Plate Nickel
- P2/P4 Connector: Serial ATA Female 7Pin  
- Pin G/F  
- Crimp type connector  
- Insulator Black
- Screw: M3.0\*10MM (M3.0 screwcap)

**Electrical:**

- 100% Open Short & Miswire Test
- Conductive Resistance: 2Ω (Max.)
- Insulation Resistance: 5MΩ (Min.)
- Hi-Pat Test 300V DC

Scale	1:1							Name	Item No.						
TOLERANCE								Chappell	<b>AK-ESATA-SB2-R</b>						
X.X	±0.40						Drawn	12.29.11							
X.XX	±0.25						Approved								
X.XXX	±0.15														
Angle	±3°														
<table border="1"> <tr> <td>Modification</td> <td>Date</td> <td>Name</td> </tr> </table>									Modification	Date	Name	<table border="1"> <tr> <td>Drawing No.</td> <td rowspan="2"><b>rev00</b></td> </tr> <tr> <td>Replace</td> </tr> </table>	Drawing No.	<b>rev00</b>	Replace
Modification	Date	Name													
Drawing No.	<b>rev00</b>														
Replace															

