



DATE BY 89/9.15	REVISION ▲
--------------------	---------------

- MAT'L:
- 1.CABLE:#28,UL2919,3COAX+4C+1+AL/MY+B,O.D:8.1
  - 2.CONNCTOR:HD15M,9th EMPTY,BLACK HD15F,BLACK
  - 3.THUMBSCREW:#4-40UNC,E32
  - 4.COPPER TAPE:30 X 50
  - 5.BLACK HEAT SHRINK TUBE:Ø1.5x15:6PCS Ø3x8:6PCS

- NOTE:
- 1.TOTAL LENGTH:1800±50mm
  - 2.COLOR:BEIGE
  - 3.MOLDED TYPE
  - 4.360° SOLDER

CONFIGURATION:

HD15M		HD15F
1	RED(COAX.)	1
6	RED(GROUND)	6
2	GREEN(COAX.)	2
7	GREEN(GROUND)	7
3	BLUE(COAX.)	3
8	BLUE(GROUND)	8
4	BROWN	4
5	BLACK	5
13	ORANGE	13
14	WHITE	14
SHIELD	(BRAID)	SHIELD

▲ \*MODIFY:BUYER NO:CC401M1-37(AK3220 1.8M) AK3220-1.8M,  
DESIGNATE INNER CORD COLOR(M00092) Y.C.C/89.9.15

④	THUMBSCREW:#4-40UNC,E32	4
③	#28,UL2919,3COAX+4C+B,O.D:8.1,BEIGE	1.8M
②	HD15F,BLACK	1
①	HD15M,9th EMPTY,BLACK	1
NO.	DESCRIPTION	QTY

DATE	19 JUN,1996	PARTS NO	MN3043N	TITLE:	HD15 MALE-HD15 FEMALE (MD TYPE)	DRAWN	S.M. 6/19	CHECK	APPRO	
UNIT	MM	DRAWN NO	001142			<b>ASSMANN ELECTRONICS.INC</b>				
SCALE		BUYER NO	002		<b>AK3220 1.8M</b>					