


1 2 3 4 5 6 7



Material:

- Cable: UL-2725 [#28(7/0.1 27 T.C)*1P INS:Foam-PE+D.W (7/0.127 T.C)+AL/MY+Hot-melt-Mylar]*2C+#28(7/0.127 T.C)*1P INS:Polyolefin + #28(7/0.127 T.C)*2C INS:Polyolefin + AL/MY +B.D(85%)

- PVC Jacket
- OD: 5.2±0.15MM
- Color: Black
- P1 & P2 Connectors: USB 3.0 A Male 9 Pin
 - Contact: 30μ"
 - Shell: Ni-Plated
- Hood: Molded Type, PVC 45P (Black)

Electrical:

- 100% Open short & mis wire test
- Contact Resistance: 3Ω Max.
- Insulation Resistance: 10MΩ Min.
- Hi-Pot 300V DC

PIN OUT	
P1	P2
1 RED	1 VCC
2 WHITE	2 -DATA
3 GREEN	3 +DATA
4 BLACK	4 GND_PWRrt
5 BLUE	8 SDP1-
6 YELLOW	9 SDP1+
7 D.W	7 SDP1_Drain
8 PURPLE	7 SDP2_Drain
9 ORANGE	5 SDP2-
SHELL B.D	6 SDP2+
SHELL	SHELL

Unit: mm



Scale	Free					Date	Name
TOLERANCE					Drawn	24.09.13	Wilson
X.	±0.3				Approved	24.09.13	Groll
X.X	±X						
X.XX	±X						
DIM	TOL						
X.°	±X°						
X.X°	±X°						
Angle	TOL	Id.	Modification	Date			

Title	
USB 3.0 cable	
A type Male to Male, 9 pin, 3 Meters	
ASSMANN WSW-No.	
AK670/3-3	
Drawing-No.	rev00
Replace	Sheet 1/1

1 2 3 4 5 6 7