


# Vertical Male




## Series 7200 – Style B 19, 133 Contacts




- Up to 95 signal contacts and 38 ground shield contacts in 5 or 5+2 rows of 19 positions
- Designed for gas tight press-fit installations
- This connector fills position P3 of the CompactPCI® specification and should be used with a type A or AB connector
- Twelve different contact styles are available for customizing connector to exact specifications (complete form on page 58)
- This connector also fills position J0 of the VME64 Extension Specification



**DIMENSIONS: millimeters (inches)**



**LAYOUT**



# Vertical Male

## Style B 19 – 133 Contacts



Pin Loading	Contacts	Performance Class	Part Number
<p><b>P3 CompactPCI®</b></p>	133	2	17 7200 133 300 002
<p><b>P3 CompactPCI®</b></p>	133	2	17 7200 133 301 002
<p><b>P3 CompactPCI®</b></p>	133	2	17 7200 133 302 005
<p><b>P3 CompactPCI®</b></p>	133	2	17 7200 133 303 005
<p><b>P3 CompactPCI®</b></p>	133	2	17 7200 133 304 005
	95	2	17 7200 095 300 012

Technical description and dimensions see page 38

AVX will custom load connectors with any combination of the contacts in the table below. Complete the form on page 57 and fax it to the number shown.

