

Fully Managed Industrial Ethernet Switch

10/100M, Gigabit Uplink, PoE+, SNMP, Modbus/TCP

Model SECP510-2SFP-T

B+B SMARTWORX

Powered by

ADVANTECH

www.advantech-bb.com



SECP510-2SFP-T



e\worx

Features & Benefits

- 8-port 10/100Mbps + 2-port Gigabit Combo (RJ45 or SFP) Uplink
- Full suite of Layer 2 functionality and advanced diagnostic tools
- IEEE802.3af/at PoE/PoE+ standard compliant, up to 120W as total PoE power budget
- Smart PoE Management, allowing to reboot PD (Powered Device) device remotely.
- Energy Efficient Ethernet (EEE), IEEE 802.3az for low energy consumption
- Jumbo Frame support, up to 9,216 bytes
- IXM™ function enables the cross management for fast deployment
- X-Ring™ function offers self-healing recovery time less than 20 ms
- Redundant Power Inputs (16.8 - 57.6 VDC)
- Wide Temperature Range -40 to 75°C
- EMS Level 3 Radiated/Conducted noise protection
- Designed for UL508 (Industrial Control Panel), NEMA TS2 (Traffic Control), EN50121-4 (Rail Signal Control)



Introduction

The SECP500 series is a fully managed PoE+ Gigabit Ethernet switch with industrial, ruggedized features designed to work in harsh environment applications. This switch offers all the features expected in a managed switch such as VLAN, IGMP Snooping, Network Redundancy, Link Aggregation, SNMP V1,V2c,V3, Web and Telnet support. Smart PoE Management features allow advanced PoE settings and monitoring. Comprehensive network security features such as SSH, HTTPS/SSL, TLS, TTLS, PEAP and Radius are also offered.

The SECP500 series support Power over Ethernet, simplifying deployments with PTZ cameras, wireless access points (APs), and other standards-compliant powered devices. The products comply with the 802.3af/at PoE+ standards, supporting up to 30W on each PoE port, not to exceed the switches specific power budget. Using the management interface, an administrator can control various PoE functions, such as remotely rebooting cameras or access points, from anywhere on the network, including over the Internet.

SECP500 series switches features a powerful suite of diagnostic, monitoring, network performance capabilities and industry leading eWorx IXM™ cross management technology: Cable diagnostics, IPv4/IPv6 ping, fiber SFP monitoring (DDMI), port utilization, traffic statistics, QoS and rate limiting - all available from the Web GUI. IXM™ also allows the installer to auto synchronize firmware updates and push configuration settings to either individual or groups of switches.

Outstanding L2 Managed Feature Design

IEEE802.3az – Energy-Efficient Ethernet (EEE) is a set of enhancements to the twisted-pair and backplane Ethernet family of computer networking standards that allows for less power consumption during periods of low data activity.

Smart PoE Management – The PoE management features allow the user to use the management interface, an administrator can control various PoE functions such as the power budget per port, priority, classification and monitor of PoE status such as the voltage, current, power and temperature per port.

IXM™ – Offers auto synchronization function of firmware and configuration settings to make middle/large-scale deployment of multiple switches fast and easy. A built-in Web GUI feature, no need for extra software to be installed on a computer.

X-Ring™ – Sub-20ms self-healing/ring recovery technology. X-Ring™ supports different topology options and allows different ring healing methods to coexist in one switch - Couple Ring, Dual Homing and Multi-couple Ring - reduce redundant network cabling and planning costs and ensure high reliability of your industrial network applications.

Multiple Account Access – This feature allows the network manager to create user accounts with differing permissions. User ID's can be created with a wide variety of access - from simple device monitoring to full maintenance accessibility, thus ensuring security and offering flexibility for field deployment.

IPv6 – A future-proof feature, IPv6 (Internet Protocol version 6) is a set of specifications from the Internet Engineering Task Force (IETF) that is an upgrade of IP version 4 (IPv4). The basics of IPv6 are similar to those of IPv4 - devices can use IPv6 as source and destination addresses to pass packets over a network.

IGMP Snooping – The Internet Group Management Protocol is a feature that allows the managed switch to forward and filter multicast traffic intelligently, designed for the video streaming and automation control network applications.

DDM – Digital-diagnostic-monitoring ("digital optical monitoring" or DOM) provides a user with critical information concerning the status of transmitted and received signals. This approach allows for better fault isolation and error detection.

Cable Diagnostics – This feature enables you to verify the length of a cable right from the switch to the other end. This is essential in diagnosing faults as a break in the cable can be easily identified on a single wire within the cable, as well as shorts and crossed-pairs.

Dual Image – Considering possible failures during FW upgrades, such as power failure or human error, dual image provides a backup image in case the system can't boot up through the primary image. The system automatically switches to the backup image to reduce downtime.

Embedded Watchdog Timer – This feature, embedded into our managed switches, when the user can't easily access the field switch or would be unable to react to faults in a timely manner. Detect and recover from switch malfunctions.

Ease of Use – 10/100BaseTX or 10/100/1000Mbps ports are auto sensing and auto configuring. Each copper port is automatically negotiated for maximum speed and performance by default, but can also be configured individually via the user interface. A powerful inside processor allows wire speed capability on all.

All product specifications are subject to change without notice.
SE500_100 GB-SFP_5016ds

Specifications

COMMUNICATIONS	
Standards	IEEE 802.3, 802.3u, 802.3x, 802.3ab, 802.3z, 802.1p, 802.3az, 802.1w, 802.1s, 802.1Q, 802.1X, 802.1ad, 802.3af, 802.3at
LAN	10/100/1000Base-T(X), Optional 100Base-FX, 1000Base-SX/LX/LHX/XD/ZX/EZX
Transmission Distance	Ethernet: 100m (4-wire Cat.5e, Cat.6 RJ-45 cable for GB port) SFP: 110km (depends on SFP)
Transmission Speed	Ethernet: 10/100Mbps Auto-Negotiation Gigabit Copper: 10/100/1000Mbps, Auto-Negotiation Gigabit Fiber: Up to 1000Mbps
INTERFACE	
Connectors	8 x RJ45 + 2 x (RJ45/SFP) combo ports 1 x RS-232 Console port (RJ45 connector) 1 x Reset bottom 6-pin removable screw terminal (power & relay)
Ethernet	Auto Sensing, 10/100BaseTX, 10/100/1000BaseTX, Duplex, MDIX
LED Indicators	PWR1, PWR2, SYS, Alarm and R.M. 10/100T(X): Link/Activity, Speed, PoE Gigabit Copper: Link/Activity, Speed SFP: Link/Activity

B+B SMARTWORX

Powered by

ADVANTECH

orders@advantech-bb.com
support@advantech-bb.com

Corporate Headquarters: 707 Dayton Road, PO Box 1040 Ottawa, IL 61350 USA 815-433-5100 Fax 433-5104
European Office: Westlink Commercial Park, Oranmore Co. Galway Ireland +353 91 792444 Fax +353 91 792445

Fully Managed Industrial Ethernet Switch

10/100M, Gigabit Uplink, PoE+, SNMP, Modbus/TCP

Model SECP510-2SFP-T

Software Specifications

SWITCH PROPERTIES	
MAC Table Size	8K
Packet Buffer Size	4.1Mbit
Switching Capacity	5.6Gbps
Jumbo Frame	9,216 bytes
Priority Queues	8
Max. Number of Available VLANs	256
VLAN ID Range	VID 1 to 4094
IGMP Groups	256
SOFTWARE	
Management	Web interface, Serial interface (Console), WebAccess NMS™, Multiple user accounts, LLDP, SNMP v1/v2c/v3, Traps, SMTP, RMON, Smart PoE management, SNT, Standard MIB, Private MIB
Configuration	HTTP/TFTP, Command line interface (CLI), IPv4/IPv6, TELNET, DHCP server/ client, DHCP option 66/67/82, Flow control, Ingress/Egress Rate limit, Jumbo frame
Security	802.1x, IP Security (Trusted Host), DoS prevention, HTTPS/SSL, SSH, PEAP, RADIUS, Multiple account setting, Storm control, Port-IP Binding, SNMPv3 (Encryption)
Redundancy	X-Ring™ (Self-Recovery time < 20 ms), STP/RSTP/MSTP, LACP(Link Aggregation Control Protocol)
Monitoring	Port statistics & utilization, LLDP/IGMP/MLD statics, Loop detection, Power status
Filter	Multicast (IGMP Snooping/Querier), Unknown multicast filtering, 802.1Q VLAN, Port-based VLAN, GVRP, GARP, Q in Q, QoS (IEEE 802.1p) with 8 classes and TOS/DiffServ, Flow control
Industrial Protocol	Modbus/TCP
Diagnostics	Cable Diagnostic, IPv4/IPv6 Ping Test, Syslog, Port Mirror, DDM (Digital-Diagnostic-Monitoring), Port Mirroring 1:1 and N:1
Enhanced Provisioning	IXM™ Cross management platform for fast deployment, Configuration backup manager, Import/ Export configuration files, firmware upgrades
Miscellaneous	Remote reboot/reset device, Dual Image, Embedded watchdog timer, Multiple account setting (Admin/User)

Hardware Specifications

POWER	
Power Consumption	Max. 132W (PoE on), 12.1W (PoE off)
Power Input	24~48 VDC (16.8~57.6 VDC) dual inputs
Fault Output	1 Relay Output
Reverse Polarity Protection	Present
Overload Current	Present
POE (POWER OVER ETHERNET)	
PoE Standard	IEEE802.3af/at (Alternative A)
PoE Pins	With data pairs, 1, 2 and 3, 6
PoE Power Budget	Max. 120W - SECP510-2SFP-T Max. 30W - each port
PHYSICAL	
Dimensions (WxHxD)	74 x 152 x 105 mm (2.91 x 5.98 x 4.13 inches)
Protection Class	IP30
Weight	Net: 1.3 kg, Gross: 1.8 kg
Enclosure	Metal Shell
Mounting	DIN Rail, Wall
ENVIRONMENT	
Operating Temperature	-40 to +75°C (-40 to +167°F)
Storage Temperature	-40 to +85°C (-40 to +185°F)
Operating Humidity	10 to 95% (non-condensing)
Storage Humidity	10 to 95% (non-condensing)
MTBF	858,835 hours
CERTIFICATIONS	
Safety	UL508
Traffic Control	NEMA TS2
Rail Signal Control	EN50121-4
EMI	FCC Part 15 Subpart B Class A, EN 55011/55022, Class A
EMS	EN 61000-4-2 (Level 3), EN 61000-4-3 (Level 3) EN 61000-4-4 (Level 3), EN 61000-4-5 (Level 3) EN 61000-4-6 (Level 3), EN 61000-4-8 (Level 3)
Shock	IEC 60068-2-27
Freefall	IEC 60068-2-32
Vibration	IEC 60068-2-6

Product Ordering Information

MODEL #	DESCRIPTION	OPERATING TEMPERATURE	RJ45		FIBER		CONNECTOR
			10/100/1000 MBPS	POE/POE+ (PSE)	100/1000BASE-SFP	COMBO PORT, 10/100/1000BASE-T(X) OR 100/1000BASE-SFP	
SECP510-2SFP-T	8-port 10/100 Mbps + 2 GbE Combo Full PoE+ Managed Ethernet Switch, 120W PoE Budget	-40 to +75°C	8	Up to 30W per port	-	2	LC (SFP)

Accessories - Optional (sold separately)

MODEL #	DESCRIPTION	OPERATING TEMPERATURE
SDR-240-24	DIN Rail Power Supply, 24VDC, 240W, 5A	-20~70 °C
SDR-240-48	DIN Rail Power Supply, 48VDC, 240W, 10A	-20~70 °C
SDR-480-24	DIN Rail Power Supply, 24VDC, 480W, 20A	-20~70 °C
SDR-480-48	DIN Rail Power Supply, 48VDC, 480W, 10A	-20~70 °C

Accessories - WebAccess/NMS, Networking Management Software (sold separately)

MODEL #	DESCRIPTION
Trial Version	6 Months Free Trial -- ask your local sales representative
NMS-U050-ULE	Supports maximum 50 nodes
NMS-U300-ULE	Supports maximum 300 nodes
NMS-U01K-ULE	Supports maximum 1,000 nodes
NMS-U04K-ULE	Supports maximum 4,000 nodes

Package Checklist

Ethernet Switch, RJ45 to DB9 console port cable, Protective Caps for unused ports, Quick Start Guide, DIN-Rail mount bracket (installed), wall mount bracket.

Warranty

Limited lifetime warranty for B+B SmartWorx designed and/or manufactured products.

Small Form Pluggable (SFP) Modules

Copper SFP (10/100/1000 and 1000 Mbps)

Fiber SFP (155 Mbps, 1.25 Gbps)

- Future-proof network equipment
- Available in SM, MM fiber types
- Maximize network hardware
- Troubleshooting diagnostics
- Plug-and-play operation



Copper

Fiber LC

SFPs are compact transceivers that function as modular connectors. Available for copper (RJ-45) and all common fiber modes, wavelengths and data rates, these modules allow network operators to connect different interface types to the same network equipment via an SFP port. The cost of cable upgrades is greatly reduced, preserving the networking equipment investment – all for the price of a relatively inexpensive module.

More and more network equipment is being designed with SFP ports to take advantage of the inherent flexibility and to eliminate the guesswork and uncertainty of expensive equipment purchases. Remember to select an SFP to match the speed of your designated port. All modules from B+B SmartWorx carry a limited lifetime warranty.

Standard Diagnostics

- SFP Type
- Fiber Link Length
- Wavelength
- Bit Rate
- Date Code

DDMI/Extended Diagnostics

- Temperature
- Voltage
- Bias Current
- TX Power
- RX Power

Fiber SFP Modules

Robust Industrial Performance

- Extended operating temperature range
- Hot swappable

Feature Friendly

- Available in a wide range of fiber types, wavelengths and transmission rates to meet almost any networking need

Extended Diagnostics

- Powerful troubleshooting Digital Diagnostics Monitoring Interface (DDMI)

Standard Compliances

- MSA compliant: available in dual- or single-strand, SC or LC connector
- Eye Safety meets Laser Class 1 Compliance with IEC 60825-1
- Complies with Telecordia GR-468-CORE
- RoHS compliant

Voltage/Temperature

- Input Voltage: 3.3V
- Operating Temperature: -40° to +85° C
- Operating Temperature, CWDM: 0° to +70° C
- Storage Temperature: -40° to +85° C

Data Rates

- 155 Mbps
- ITU-T G.957, G.958 and IEEE 802.3u
 - Applications: Fast Ethernet, OC-3/STM-1 and other optical links
- 1.25 Gbps
- Compliant with specifications for IEEE 802.3z
 - Applications: Gigabit Ethernet and other optical links

Copper SFP Models

MODEL NUMBER	PORT DESCRIPTION	CONNECTOR	DISTANCE
808-39001	10 - 1250, TX	RJ45	100 m
808-39010	1250, TX	RJ45	100 m

IE-SFP Modules: 100 to 155 Mbps, DDMI (OC-3)

MODEL NUMBER	PORT DESCRIPTION	FIBER	DISTANCE	POWER BUDGET
				<i>(db)</i>
<i>W/ DDMI</i>				
808-38101	MM850	LC	2 km	14.5
808-38102	MM1300	LC	2 km	11
808-38103	SM1310	LC	20 km	21
808-38104	SM1310/PLUS	LC	40 km	31
808-38105	SM1550/LONG	LC	80 km	31

IE-SFP Modules: 1.25 Gbps GB Ethernet, DDMI (OC-24)

MODEL NUMBER	PORT DESCRIPTION	FIBER	DISTANCE	POWER BUDGET
				<i>(db)</i>
<i>W/ DDMI</i>				
808-38201	MM850	LC	220/550 m	7.5
808-38206	MM1300	LC	2 km	10
808-38200	SM1310	LC	20 km	14
808-38203	SM1310/PLUS	LC	30 km	17
808-38204	SM1550/LONG	LC	40 km	18
808-38205	SM1550/XLONG	LC	70 km	21
808-38208	SM1550/XXLONG	LC	120 km	30

IE-SFP Modules: CWDM (155 Mbps/1.25 Gbps), DDMI

MODEL NUMBER	DESCRIPTION	FIBER	DISTANCE	POWER BUDGET (db)
			<i>155 Mbps</i>	<i>1.25 Gbps</i>
			<i>Mbps</i>	<i>Mbps</i>
808-38141	808-38241	CWDM-SM1270	LC 80 km	40 km 29 22
808-38142	808-38242	CWDM-SM1290	LC 80 km	40 km 29 22
808-38143	808-38243	CWDM-SM1310	LC 80 km	40 km 29 22
808-38144	808-38244	CWDM-SM1330	LC 80 km	40 km 29 22
808-38145	808-38245	CWDM-SM1350	LC 80 km	40 km 29 22
808-38146	808-38246	CWDM-SM1370	LC 80 km	40 km 29 22
808-38147	808-38247	CWDM-SM1390	LC 80 km	40 km 29 22
808-38148	808-38248	CWDM-SM1410	LC 80 km	40 km 29 22
808-38149	808-38249	CWDM-SM1430	LC 80 km	70 km 29 22
808-38150	808-38250	CWDM-SM1450	LC 80 km	70 km 29 22
808-38151	808-38251	CWDM-SM1470	LC 80 km	70 km 29 22
808-38152	808-38252	CWDM-SM1490	LC 80 km	70 km 29 22
808-38153	808-38253	CWDM-SM1510	LC 80 km	70 km 29 22
808-38154	808-38254	CWDM-SM1530	LC 80 km	70 km 29 22
808-38155	808-38255	CWDM-SM1550	LC 80 km	70 km 29 22
808-38156	808-38256	CWDM-SM1570	LC 80 km	70 km 29 22
808-38157	808-38257	CWDM-SM1590	LC 80 km	70 km 29 22
808-38158	808-38258	CWDM-SM1610	LC 80 km	70 km 29 22

NOTES: Fiber SFP Form Factors & Distances

Fiber SFP (OC-3, OC-24) form factors have virtually identical dimensions and are not typically interchangeable; this will depend on the device type.

For each fiber product listed in the tables, DISTANCE represents an approximate fiber distance based on industry-standard fiber attenuation specifications. Actual distances will vary for each installation. For complete power budgets and additional information on calculating specific distances, contact B+B SmartWorx Technical Support specialists at (815) 433-5100 (USA).

Fully Managed Industrial Ethernet Switch

10/100M, Gigabit Uplink, PoE+, SNMP, Modbus/TCP

Model SECP510-2SFP-T

Model SECP510-2SFP-T Mechanical Diagram | DIN Rail & Wall Mount Options

Units = [inches] mm

