



NOTES:
 1. SWITCH RATING: 1A, 125VAC, 30VDC
 UL, CSA
 2. CHARACTERISTICS MEASURED AT POINT "A".

REVISIONS		3TMT7084		REV. A
ECN	SYM	DESCRIPTION	DATE	BY
52424	A	CREATE NEW DRAWING	12-OCT-98	SUE

OPERATE FORCE GRAMS	80 MAX
RELEASE FORCE GRAMS	16 MIN
RETURN FORCE GRAMS	9 MIN
DIFF MOTION MAX IN./MM	.032 / 0.813
PRETRAVEL MAX IN./MM	.200 / 5.080
OVERTRAVEL MIN IN./MM	.060 / 1.524

CAD FILE NO.: 3tmt7084_a

ALL DIMS. AND TOLS. PER ANS I Y14.5 THIS DOCUMENT AND THE INFORMATION IT CONTAINS IS THE EXCLUSIVE PROPERTY OF C&K COMPONENTS, INC., AND IS NOT TO BE USED OR DISCLOSED WITHOUT THE EXPRESS WRITTEN PERMISSION OF C&K COMPONENTS, INC.	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES DECIMAL .XXX ± .015 ANGULAR ± 1° SCALE 2:1 DATE 12-OCT-98 DRAWN SUE	3TMT7084 	REV. A SHT. NO. 1 OF 1 3TMT7084 SHT. NO. 1 OF 1
---	--	---------------------	--