



2P-2T



示意图SCHEMATIC



安装孔PIERCING PLAN

规格 Specifications

额定负荷 Ratings	DC 30 V 0.1 A
初期接触电阻 Initial Contact Resistance	80 mΩ Max.
绝缘电阻 Insulation Resistance	DC 500 V 60 Sec. 100 MΩ Min.
抗电强度 Dielectric Voltage	AC 500 V(50~60HZ) 60 Sec.

操作力 Operating Force	150±50gf
负荷寿命 Operating Life With Load	10,000 次 Cycles

序号 NO.	零件 PART	材料 MATERIAL	数量 QTY	备注 REMARKS	标号 REV	内容 DESCRIPTION	签名 SIGN.	日期 DATE
07	端子 TERMINAL	C2680R	6	Ag PLATED				
06	锁针 LOCK HOOK	SUS	1	NATURAL				
05	胶壳 HOUSING	PA	1	BLACK C				
04	接触片 CONTACT	C5210R	2	Ag CLAD				
03	胶盖 COVER	PA	1	BLACK C				
02	弹簧 SPRING	SUS	1	NATURAL				
01	胶柄 KNOB	POM	1	NATURAL				
					DWG NO. ITEM3141			

TOLERANCES UNLESS OTHERWISE SPEC.		TITLE	PUSH SWITCH		ITEM NO	PS-2214-L NS PA		
UNDER 1	± 0.10	DRAWN	张渠江	2009-12-28	VERSION	A01	PAGE 1	OF 1
1 - 10	± 0.30	REVIEWED	王光云	2009-12-28	SCALE	—	UNIT	mm
OVER 10	± 0.50	APPROVED	马建和	2009-12-28	PROJECTION			

COMAX 高铭电子(惠州)有限公司
Comax Electronics(Huizhou)Co.,Ltd.