

## Telecom OC48 Oscillator

- 622.08 MHz Osc
- CMOS Output

## Applications

- SDH / SONET
- Digital Switching
- Test Equipment
- Cellular Telephony
- Land Mobile Radio

Series **CFSC**



### Part Numbering Example: CFSC Z


**CFSC**  
SERIES

Specifications:	Min	Typ	Max	Unit
Frequency Range:		622.08		MHz
Available Stability Options:	-50		50	ppm
Supply Voltage:	3.135	3.3	3.465	V
Operating Temperature Range Options:	-10		85	°C
Storage Temperature:	-55		125	°C
Duty Cycle:	45		55	%
Start-Up Time:		3	10	mS
Aging (PPM/1st Year): Ta=25C, Vdd=3.3V			±5	
Static Discharge Voltage Mil-Std 883, method 3015	2000			V
Supply Current			40	mA
Short Circuit Current		± 50		mA
Jitter (RMS) Integrated (12KHz - 20MHz) Period		3 10	4	pS pS
Phase Noise @10KHz Offset		-118		dBc/Hz

**Output Level:** CMOS

**Packaging:** Tape & Reel

### CFSC



- |     |          |
|-----|----------|
| PIN | FUNCTION |
| 1   | NC       |
| 2   | OE       |
| 3   | GND      |
| 4   | CMOS Out |
| 5   | NC       |
| 6   | VDD      |
- DIMENSIONS ARE IN MM

Notes: Extended exposure exceeding maximum ratings may cause permanent damage and affect reliability. Operation outside of specifications is not supported.

