

CMLD6263

**SURFACE MOUNT SILICON
DUAL, ISOLATED
HIGH VOLTAGE
SCHOTTKY DIODE**




www.centrasemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CMLD6263 incorporates two galvanically isolated, high voltage, low V_F silicon diodes in a space saving SOT-563 surface mount package. These diodes are designed for fast switching applications requiring a low forward voltage drop.

MARKING CODE: 63D or 63



SOT-563 CASE

FEATURES:

- High Voltage (70V)
- Low Forward Voltage
- Galvanically Isolated

MAXIMUM RATINGS: ($T_A=25^\circ\text{C}$)

| | SYMBOL | | UNITS |
|---|----------------|-------------|--------------------|
| Peak Repetitive Reverse Voltage | V_{RRM} | 70 | V |
| Continuous Forward Current | I_F | 15 | mA |
| Peak Forward Surge Current, $t_p=1.0\text{s}$ | I_{FSM} | 50 | mA |
| Power Dissipation | P_D | 250 | mW |
| Operating and Storage Junction Temperature | T_J, T_{stg} | -65 to +150 | $^\circ\text{C}$ |
| Thermal Resistance | θ_{JA} | 500 | $^\circ\text{C/W}$ |

ELECTRICAL CHARACTERISTICS PER DIODE: ($T_A=25^\circ\text{C}$ unless otherwise noted)



| SYMBOL | TEST CONDITIONS | MIN | TYP | MAX | UNITS |
|----------|---|-----|-----|-----|-------|
| I_R | $V_R=50\text{V}$ | | 10 | 200 | nA |
| BV_R | $I_R=10\mu\text{A}$ | 70 | | | V |
| V_F | $I_F=1.0\text{mA}$ | | 395 | 410 | mV |
| C_J | $V_R=0, f=1.0\text{MHz}$ | | | 2.0 | pF |
| t_{rr} | $I_R=I_F=10\text{mA}, I_{rr}=1.0\text{mA}, R_L=100\Omega$ | | | 5.0 | ns |

CMLD6263

**SURFACE MOUNT SILICON
DUAL, ISOLATED
HIGH VOLTAGE
SCHOTTKY DIODE**



SOT-563 CASE - MECHANICAL OUTLINE



| SYMBOL | INCHES | | MILLIMETERS | |
|--------|--------|-------|-------------|------|
| | MIN | MAX | MIN | MAX |
| A | 0.0027 | 0.007 | 0.07 | 0.18 |
| B | 0.008 | | 0.20 | |
| C | 0.017 | 0.024 | 0.45 | 0.60 |
| D | 0.059 | 0.067 | 1.50 | 1.70 |
| E | 0.020 | | 0.50 | |
| F | 0.059 | 0.067 | 1.50 | 1.70 |
| G | 0.043 | 0.051 | 1.10 | 1.30 |
| H | 0.006 | 0.012 | 0.15 | 0.30 |

SOT-563 (REV: R2)

LEAD CODE:

- 1) Anode D1
- 2) NC
- 3) Anode D2
- 4) Cathode D2
- 5) NC
- 6) Cathode D1

MARKING CODE: 63D or 63





R7 (11-December 2015)

CMLD6263

SURFACE MOUNT SILICON
DUAL, ISOLATED
HIGH VOLTAGE
SCHOTTKY DIODE



TYPICAL ELECTRICAL CHARACTERISTICS





R7 (11-December 2015)

CMLD6263

SURFACE MOUNT SILICON
DUAL, ISOLATED
HIGH VOLTAGE
SCHOTTKY DIODE



TYPICAL ELECTRICAL CHARACTERISTICS



R7 (11-December 2015)

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centalsemi.com

Worldwide Field Representatives:
www.centalsemi.com/wwreps

Worldwide Distributors:
www.centalsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centalsemi.com/terms



<http://www.centrasemi.com>

PDN01063 Rev:001

3/03/17

N/A

N/A

Please be advised that Central Semiconductor must immediately discontinue the product(s) listed in the attached PDN notice. We are unable to accept any further orders for these products **unless** we have available inventory on hand.

You may have purchased one or more of the products listed. Please do not hesitate to contact your local Central Semiconductor sales representative with any questions or needs you may have. Central regrets any inconvenience this may cause.

Sincerely,

Central Semiconductor Corp.

Summary: All devices manufactured in the SOT-563 package, using the Option 2 Lead Frame, are discontinued and now classified as End of Life (EOL). Rev001 issued to include BK devices previously excluded in error.

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by various manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's Product Management Process. Any replacement product will be noted below. The effective date for placing the last purchase order will be six(6) months from the date of this notice and twelve(12) months from the notice date for final shipments; this may be extended if inventory is available.

| <u>Central Part Number</u> | <u>Replacement</u> |
|----------------------------|--------------------|
| CMLD2004G BK | N/A |
| CMLD2004G TR | N/A |
| CMLD4448 BK | N/A |
| CMLD4448 TR | N/A |
| CMLD6001 BK | N/A |
| CMLD6001 TR | N/A |
| CMLD6263 BK | N/A |
| CMLD6263 TR | N/A |
| CMLD6263S BK | N/A |
| CMLD6263S TR | N/A |
| CMLSH-4 BK | N/A |
| CMLSH-4 TR | N/A |
| CMLZDA3V3 BK | N/A |
| CMLZDA3V3 TR | N/A |
| CMLZDA6V2 BK | N/A |
| CMLZDA6V2 TR | N/A |

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. Please email your requests to engineering@centrasemi.com.