

## 1. Scope of Application

These specifications apply to chip type LED lamp, CITILED, model CL-482S-TD2-CD-TS.

## 2. Part code

Reference

**CL-482S-TD2-C D-TS**

Series

482S: Mono-color  
Ultra small, thin, sideways  
light emission type

Lighting color

TD2 : Top high brightness orange

Color of lens

C : colored

Diffusion


D : Diffused

Shipping mode

Non-coded: Bulk  
TS: Taping (standard)

			Approved	Checked	Drawn	Symbol	CITILED
						Name	CL-482S-TD2
Mark	Date	Description	Appro.	CITIZEN ELECTRONICS CO.,LTD.			

## 3. Outline drawing



## 4. Performance

## (1) Absolute Maximum Rating

(Ta=25°C)

Parameter	Symbol	Rating Value	Unit
Power Dissipation	Pd	78	mW
Forward Current	I <sub>F</sub>	30	mA
Forward Pulse Current *	I <sub>FP</sub>	100 *	mA
Reverse Voltage	V <sub>R</sub>	4	V
Operating Temperature	T <sub>OP</sub>	-25 ~ +80	°C
Storage Temperature	T <sub>st</sub>	-30 ~ +85	°C

\* Duty  $\leq 1/10$ , Pulse width  $\leq 0.1$  msec

## (2) Electro-optical Characteristic

(Ta=25°C)

Parameter	Symbol	Condition	MIN	TYP	MAX	Unit
Forward Voltage	V <sub>F</sub>	I <sub>F</sub> =20mA	—	2.1	2.68	V
Reverse Current	I <sub>R</sub>	V <sub>R</sub> =4V	—	—	100	μA
Luminous Intensity *	I <sub>V</sub>	I <sub>F</sub> =20mA	23	110	—	mcd
Dominant Wavelength	λ <sub>d</sub>	I <sub>F</sub> =20mA	595	605	615	nm

\* In accordance with NIST standard

Note 1) The tolerance of Forward Voltage measurement is  $\pm 3\%$  at our tester.Note 2) The tolerance of Luminous Intensity measurement is  $\pm 10\%$  at our tester.Note 3) The tolerance of Dominant Wavelength measurement is  $\pm 2$ nm at our tester.

Note 4) For handling, please apply CMOS LSI or equivalent to prevent any electrostatic effect.

Note 5) Please be aware that the above electro-optical characteristics are guaranteed when applying the current values shown in the table.


Please consult us when this product is used under any other conditions.

			Approved	Checked	Drawn	Symbol	CITILED
						Name	CL-482S-TD2
						Drawing No	
Mark	Date	Description	Appro.	CITIZEN ELECTRONICS CO.,LTD.			


## 5. Characteristic

Reference


IF-VF Characteristics




VF-Ta Characteristics




IV-IF Characteristics




IV-Ta Characteristics



IF Max-Ta Characteristics



Directive Characteristics



			Approved	Checked	Drawn	Symbol	CITILED
						Name	CL-482S-TD2
						Drawing No	
Mark	Date	Description	Appro.	CITIZEN ELECTRONICS CO.,LTD.			

## 6. Reliability

Reference

## (1) Details of the tests

Test Item	Test Condition
Life Test in Continuous Operation	$25 \pm 3^{\circ}\text{C}$ , $I_F = 30 \text{ mA} \times 500^{+24}_{-12}$ hours
Low Temperature Storage Test	$-30^{+3}_{-5}^{\circ}\text{C} \times 500^{+24}_{-12}$ hours
High Temperature Storage Test	$85^{+5}_{-3}^{\circ}\text{C} \times 500^{+24}_{-12}$ hours
Moisture-proof Test	$60 \pm 2^{\circ}\text{C}$ , $90 \pm 5\% \text{RH}$ for $500^{+24}_{-12}$ hours
Thermal Shock Test	$-30^{\circ}\text{C} \times 30 \text{ minutes} - 85^{\circ}\text{C} \times 30 \text{ minutes}$ , 5-cycle
Solder Heat Resistance Test	Recommended temperature profile (reflow soldering) $\times 2$ , (2 <sup>nd</sup> test must be started after the samples are stabilized thermally.)

## (2) Judgment Criteria of Failure for Reliability Test

Measuring Item	Symbol	Measuring Condition	Judgement Criteria for Failure
Forward Voltage	$V_F$	$I_F = 20 \text{ mA}$	$> U \times 1.2$
Reverse Current	$I_R$	$V_R = 4 \text{ V}$	$> U \times 2$
Luminous Intensity	$I_V$	$I_F = 20 \text{ mA}$	$< S \times 0.5$

U means the upper limit of the specified characteristics. S means the initial value.

Note: Measurement shall be taken between 2 hours and 24 hours, having returned the test pieces to the normal ambient conditions after the completion of each test.

			Approved	Checked	Drawn	Symbol	CITILED
						Name	CL-482
						Drawing No	
Mark	Date	Description	Appro.	CITIZEN ELECTRONICS CO.,LTD.			




Reference

8. Packing Specifications

8-1. Moisture-proof Packing

To prevent moisture absorption during transportation and storage, reels are packed in aluminum envelopes which contain a desiccant with a humidity indicator.



8-2. Storage

To prevent moisture absorption, it is strongly recommended that reels (in bulk or taped) should be stored in the dry box (or the desiccator) with a desiccant as the appropriate storage place. If not, the following is recommended.

Temperature: 5 ~ 30 °C  
Humidity: 60%RH max.

The devices should be mounted as soon as possible after unpacking. If you store the unpacked reels, please store them in the dry box or seal them into the envelop again.

8-3. Baking

If the devices have been stored over 6 months or unpacked over 7 days, it should be baked under the following conditions.

Baking conditions: 60°C × 12 hours or more (reeled one)  
100°C × 45 minutes or more (loose one)

			Approved	Checked	Drawn	Symbol	CITILED
						Name	CL-482
						Drawing No	
Mark	Date	Description	Appro.	CITIZEN ELECTRONICS CO.,LTD.			

## 9. Precautions

Reference

## 9-1. Soldering

## (1) Manual soldering

- 1) Solder of 96.5Sn 3Ag 0.5Cu is recommended.
- 2) Before soldering every time, make baking to units. By manual soldering, it is the possibility of crack due to the moisture absorption in the resin portion.
- 3) Use a soldering iron of 25W or smaller. Adjust the temperature of the soldering iron below 350°C.
- 4) Force or stress must not be applied to the resin portion while soldering.
- 5) Finish soldering within 3 seconds.
- 6) Handle the devices only after temperature is cooled down.

## (2) Lead free soldering


- 1) Following soldering paste is recommended

Melting temperature: 216 ~ 220°C.

Composition: 96.5Sn 3Ag 0.5Cu

- 2) The temperature profile at the top surface of the parts is recommended as shown below.

- 3) It is requested that products should be handled after their temperature has dropped down to the normal room temperature.



			Approved	Checked	Drawn	Symbol	CITILED
						Name	CL-482
Mark	Date	Description	Appro.	CITIZEN ELECTRONICS CO.,LTD.			

## Reference

## 9-2. Washing

(1) When washing after soldering is needed, following conditions are requested.


- a) Washing solvent: Alcohol
- b) Temperature, time: 50°C or less × 30 seconds max.  
or 30°C or less × 3 minutes max.
- c) Ultrasonic washing: 300W or less

## 9-3. Other directions

- (1) It is requested to avoid any stress added to the resin portion while it is heated.
- (2) It is requested to avoid any friction by sharp metal nail etc. to the resin portion.

## 10. Designing precautions

- (1) The current limiting resistor should be placed in the circuit so that is driven within its rating. Also avoid reverse voltage (over-current) applied instantaneously when ON or OFF.
- (2) When pulse driving current is applied, average current consumption should be within the rating. Also avoid reverse voltage applied when put off.
- (3) Recommended soldering pattern




The above dimensions are not the one which guarantee the performance of mountability.


The use of the above pattern is recommended to use after deep study at your site.

- (4) When assembling the circuit board into the finished products, care must be taken to avoid the component parts from touching other parts.
- (5) When using multiple LEDs, it is required to connect a current limiting resistor on each path which the current flows to the LEDs.


(ex-1)



(ex-2)



(ex-3)



			Approved	Checked	Drawn	Symbol	CITILED
						Name	CL-482
						Drawing No	
Mark	Date	Description	Appro.	CITIZEN ELECTRONICS CO.,LTD.			