


STRIPPING DIMENSION (b) (c)



Part-no. as per finish		
GOLD FLASH over NICKEL (c)	(d) min. 20µin HARD GOLD over (e) min. 50µin NICKEL	min. 30µin HARD GOLD over min. 50µin NICKEL
161A18009X	161B18009X	161C18009X

- (b) **NOTES:**
- (c)
1. Material: Copper alloy
  2. Finish: See table
  3. Temperature range: -55 °C to +125 °C
  4. Rated current: 3 A maximum
  5. Contact resistance: <= 10 mOhm
  6. Crimping: Use crimp tool 360X10329X  
With tool insert 360X10629X  
Selector settings: 4 for AWG 22  
3 for AWG 24  
2 for AWG 26  
1 for AWG 28

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

				tolerance	dim. in mm	
				DIN ISO 2768-m		
				date	name	
				drawn	12.03.01	Parei
1 x e	Ä4116	26.09.11	Lehm.	appd.	12.03.01	Mickenbecker
1 x d	Ä3750	15.09.10	K.H.	norm		
4 x c	Ä 3698	25.08.10	Lehm.	d-old		
2 x b	Ä 2647	11.01.07	Lehm.			
a	Original					
rev.	description	date	name	<b>CONEC</b> ®		

scale:	5:1	
material:	SEE NOTES	
title:	<b>HD CRIMP PLUG CONTACT</b> screw machined version accepts cable AWG 28-22	
dwg no:	Inventor 10	DIN-A4
	16K1A152A	sh: 1
part no:	SEE TABLE	