



**Notes:**

1. Electrical:
  - Meets EIA/TIA-568-B.2 Cat.5e Specification
- ⓑ - RJ45 Plug Operating Temperature: -40° C to +85° C
2. Materials and Finish:
  - RJ45 Plug Metal Shell: Copper Alloy, Nickel Plated
  - RJ45 Plug Plastic Housing: Clear Polycarbonate UL94 V-0
  - RJ45 Plug Contacts: Phosphor Bronze, Finish: 50u" Gold min. over Nickel
  - RJ45 Modular Boot: PVC, Color: Blue
  - Cable: Cat. 5e UTP (Unshielded Twisted Pair) AWG24 Solid, Color: Blue
3. RoHS compliant

Directive 2002/95/EC  
"RoHS"  
Compliant

THIS DRAWING MAY NOT BE COPIED, OR REPRODUCED IN ANY WAY AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION  <b>DO NOT ALTER CAD DRAWING BY HAND</b>	Customer:			Tolerance Unless otherwise specified		Scale: 1.5:1	Dim. in Inch	
	Name	Title	Approval Date	Dimensional: Angles		Autodesk Inventor	Material: See Notes	
				2008	Date	Name	Title: RJ45 Cat. 5e Ethernet Patch Cord Standard to Standard RoHS Compliant	
				Draw.	Aug. 11	Vincent Ke		
				Appd.	Aug. 11	J. Chaudry		
				Norm				
				D-old				
	b		Feb/18/2009	Vincent ke			Drawing No.: 17K1A007	DIN A3
	a	original					Part No.: 17-100904	Sheet 1/1
	Rev.	Changes	Date	Name	<b>CONEC®</b>			