


REV.	DESCRIPTION	DATE
A	NEW DRAWING	4/20/2006



SPECIFICATIONS:
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 100M OHMS MIN: 500V DC
 VOLTAGE WITHSTAND: 500V AC R.M.S. FOR 1 MINUTE
 LIFE: 5,000 CYCLES
 OPERATING TEMP: -20° ~ +85°C



TOLERANCE:
 ±0.3mm UNLESS OTHERWISE
 SPECIFIED



9615 SW Allen Blvd., Ste. 103
 Beaverton, OR 97005
 Phone: 503-643-4899
 800-275-4899
 Fax: 503-372-1266
 Website: www.cui.com

TITLE:	RCA Jack, Dual, Rt Angle, PCB Mount, Vert.		REV:	A
PART NO.	RCJ-33XXX	UNITS:	MM [INCHES]	
DRAWN BY:	ZRJ	APPROVED BY:		
		SCALE:	1:1	

COLOR INDEX				
PART NO.	INPUT X1	INPUT X2	INPUT X3	
RCJ-33234	Red Color	White Color	Yellow Color	
RCJ-33X1 X2 X3	Color X1	Color X2	Color X3	

COLOR CHART		MATERIAL	PLATING
1	Black	Brass	Nickel
2	Red	Brass	Silver
3	White	Brass	Silver
4	Yellow	Brass	Silver
5	Blue	ABS	Black Color
6	Green	ABS	Black Color
7	Orange	PBT	see color index
		PBT	see color index
		PBT	see color index

MODEL NO.	RCJ-33XXX
SCHEMATIC	