



## CY7C1041D-2XWI

Status: NRND

CY7C1041D-2XWI	
Automotive Qualified	N
Density (Kb)	4096
Frequency (MHz)	N/A
Max. Operating Temp. (°C)	85
Max. Operating VCCQ (V)	5.50
Max. Operating Voltage (V)	5.50
Min. Operating Temp. (°C)	-40
Min. Operating VCCQ (V)	4.50
Min. Operating Voltage (V)	4.50
Organization (X x Y)	256K x 16
Speed (ns)	0
Temp. Classification	Industrial

PRICING & INVENTORY AVAILABILITY					
1-9 unit Price*	10-24 unit Price*	25-99 unit Price*	100-249 unit Price*	250-999 unit Price*	1000+ unit Price*
<a href="#">Contact Sales</a>					

Availability	Quantity	Ships In	Order Now
Out of Stock	0	Please click <a href="#">here</a> to check lead times	<a href="#">Check Distributors**</a>

\* Prices are shown in United States dollars and are for budgetary use only for volume of 1ku

\*\* Check Distributors: This part is sold through distributors only.

PACKAGING/ORDERING	
No. of Pins	1
Package Cross Section Drawing	<a href="#">Download</a>
Package Carrier	TRAY
Package Carrier Drawing / Orientation	<a href="#">Package Orientation</a>
Standard Pack Quantity	5
Minimum Order Quantity (MOQ)	1
Order Increment	1

Estimated Lead Time (days)	
HTS Code	8542.90.0000
ECCN	(B.2.B.)
ECCN Suball	3A991

QUALITY AND ROHS	
Moisture Sensitivity Level (MSL)	5
Peak Reflow Temp. (°C)	
RoHS Compliant	N Print RoHS Certificate of Compliance
PB Free	N
Lead/Ball Finish	N/A
Marking	Cypress Marking Format
<b>Device Qualification Reports</b>	
FIT/MTBF, ESD (HBM/CDM) and Latch-up data available in the Device Qualification Report.	
<a href="#">QTP 052207.pdf</a> Last Update: Jun 02, 2013	