



## CY7C1444AV33-1XWI

Status: NRND

CY7C1444AV33-1XWI	
Architecture	Standard Sync, Pipeline DCD
Automotive Qualified	N
Burst Length (Words)	0
Density (Kb)	36864
Density (Mb)	36
Frequency (MHz)	N/A
Max. Operating Temp. (°C)	85
Max. Operating VCCQ (V)	3.60
Max. Operating Voltage (V)	3.63
Min. Operating Temp. (°C)	-40
Min. Operating VCCQ (V)	2.40
Min. Operating Voltage (V)	3.14
Organization (X x Y)	1Mb x 36
Temp. Classification	Industrial

PRICING & INVENTORY AVAILABILITY					
1-9 unit Price*	10-24 unit Price*	25-99 unit Price*	100-249 unit Price*	250-999 unit Price*	1000+ unit Price*
Contact Sales					

Availability	Quantity	Ships In	Order Now
Out of Stock	0	Please click <a href="#">here</a> to check lead times	<a href="#">Check Distributors**</a>

\* Prices are shown in United States dollars and are for budgetary use only for volume of 1ku

\*\* **Check Distributors:** This part is sold through distributors only.

PACKAGING/ORDERING	
No. of Pins	1
Package Cross Section Drawing	<a href="#">Download</a>

Package Carrier	Bulk
Package Carrier Drawing / Orientation	Package Orientation
Minimum Order Quantity (MOQ)	1
Order Increment	1
Estimated Lead Time (days)	
HTS Code	8542.32.0040
ECCN	(B.2.A.)
ECCN Suball	3A991

QUALITY AND ROHS	
Moisture Sensitivity Level (MSL)	5
Peak Reflow Temp. (°C)	
RoHS Compliant	N Print RoHS Certificate of Compliance
PB Free	N
Lead/Ball Finish	N/A
Marking	Cypress Marking Format