



## Spiral Wrap Plastic Tubing For Harnesses

Available from four materials: Polyethylene, Rulan (flame retardant Polyethylene), Nylon and Teflon. These insulations are easily applied by twisting them over the item(s) to be protected. They can be flexed repeatedly without cracking or breaking. Spiral Wrap is reuseable and expandable. It bends around sharp corners. Per MIL-P-21922B, MIL-I-631D, MIL-P-3803.

Cut lengths are available.

| <b>Polyethylene</b><br>This series is RoHS compliant.  |              | <b>Temp. Range: -105°F to +200°F</b> |                         |                  |                         |
|--|--------------|--------------------------------------|-------------------------|------------------|-------------------------|
| <b>Daburn Cat. No.</b>                                 |              | <b>Covers Wire Groups</b>            | <b>Outside Diameter</b> | <b>Nom. Wall</b> | <b>Standard Package</b> |
| <b>Natural</b>   | <b>Black</b> |                                      |                         |                  |                         |
| 605-1/8  | 605B-1/8     | 1/16" to 1/2"                        | 1/8"                    | .031"            | 100', 500', 1000'       |
| 605-1/4  | 605B-1/4     | 3/16" to 2"                          | 1/4"                    | .045"            | 100', 500', 1000'       |
| 605-3/8  | 605B-3/8     | 5/16" to 3"                          | 3/8"                    | .058"            | 100', 500', 1000'       |
| 605-1/2  | 605B-1/2     | 3/4" to 4"                           | 1/2"                    | .058"            | 100', 500', 1000'       |
| <b>Rulan (White)</b><br>This series is RoHS compliant. |              | <b>Temp. Range: -10°F to +200°F</b>  |                         |                  |                         |
| <b>Daburn Cat. No.</b>                                 |              | <b>Covers Wire Groups</b>            | <b>Outside Diameter</b> | <b>Nom. Wall</b> | <b>Standard Package</b> |
|  |              |                                      |                         |                  |                         |
| 606-1/8  |              | 1/16" to 1/2"                        | 1/8"                    | .030"            | 100', 500', 1000'       |
| 606-1/4  |              | 3/16" to 1 1/2"                      | 1/4"                    | .045"            | 100', 500', 1000'       |
| 606-3/8  |              | 5/16" to 2"                          | 3/8"                    | .052"            | 100', 500', 1000'       |
| 606-1/2  |              | 3/4" to 4"                           | 1/2"                    | .062"            | 100', 500', 1000'       |

|  |  |                                      |  |  |  |
|--|--|--------------------------------------|--|--|--|
| <b>Nylon</b><br><b>Per MIL-P-22692, MIL-I-20693, MIL-M-22096, MIL-M-19098</b><br><b>This series is RoHS compliant.</b> |  | <b>Temp. Range: -212°F to +300°F</b> |  |  |  |
|--|--|--------------------------------------|--|--|--|

| Daburn Cat. No. |          | Covers Wire Groups | Outside Diameter | Nom. Wall | Standard Package  |
|-----------------|----------|--------------------|------------------|-----------|-------------------|
| Natural         | Black    |                    |                  |           |                   |
| 607-1/8         | 607B-1/8 | 1/16" to 1/2"      | 1/8"             | .030"     | 100', 500', 1000' |
| 607-1/4         | 607B-1/4 | 3/16" to 2"        | 1/4"             | .025"     | 100', 500', 1000' |
| 607-3/8         | 607B-3/8 | 5/16" to 3"        | 3/8"             | .035"     | 100', 500', 1000' |
| 607-1/2         | 607B-1/2 | 3/4" to 4"         | 1/2"             | .035"     | 100', 500', 1000' |

|  |  |                                      |  |  |  |
|--|--|--------------------------------------|--|--|--|
| <b>Teflon (Natural)</b><br><b>Per MIL-I-22129, MIL-T-47287A, AMS-3653</b><br><b>This series is RoHS compliant.</b> |  | <b>Temp. Range: -450°F to +500°F</b> |  |  |  |
|--|--|--------------------------------------|--|--|--|

| Daburn Cat. No. |  | Covers Wire Groups | Outside Diameter | Nom. Wall | Standard Package |
|-----------------|--|--------------------|------------------|-----------|------------------|
| 608-1/8         |  |                    |                  |           |                  |
| 608-1/4         |  | 3/16" to 2"        | 1/4"             | .030"     | 100', 500'       |
| 608-3/8         |  | 5/16" to 3"        | 3/8"             | .030"     | 100', 500'       |
| 608-1/2         |  | 3/4" to 3"         | 1/2"             | .030"     | 100', 500'       |
| 608-3/4         |  | 11/16" to 6"       | 3/4"             | .040"     | 100', 200'       |
| 608-1"          |  | 15/16" to 8"       | 1"               | .040"     | 100', 200'       |

To [Additional insulating Tubing and Sleeving](#)

Back to DABURN'S [Home Page](#)

**Daburn electronics & cable corp.**  
**224 Pegasus Ave.**  
**Northvale, NJ 07647-1909**  
**Tel: 201-768-5400**  
**Fax: 201-768-9642**  
**E-Mail: [daburn@daburn.com](mailto:daburn@daburn.com)**  
**URL: <http://www.daburn.com>**