



## CheapDuino (SKU:DFR0236)

---



### Contents

- [1 Introduction](#)
- [2 Specification](#)
- [3 Pinout Diagram](#)
- [4 Connection Diagram](#)
- [5 Example Code](#)
- [6 FAQ](#)



### Introduction

CheapDuino is the most cheapest Arduino compatible processor in the world. It's aimed to supply a low cost processor for the students and DIYers from second and third world countries. The price for each cheapDuino controller is almost 1/5 price of the Arduino UNO. So it's also suitable for you to DIY custom project, workshop, gift for friend, E-Textiles and education usage.

## Specification

- Working voltage: 3~5 volts
- Recommended power supply: 5v
- Microcontroller: Atmel AVR ATmega8
- bootloader(Board option in Arduino IDE): Arduino NG / w ATmega8
- 3 digital pins, 3 analog pins with easy-to-solder hexagonal pads
- Integrate 3 pwm pins, I2C interface and UART interface
- Suitable for workshop, education usage and DIY custom projects
- Low cost Arduino compatible controller
- Designed for the students and DIYers from second and third world countries
- Dimensions: 2cm x 2cm x 0.2cm

## Pinout Diagram



## Connection Diagram




Fig1: cheapDuino Pin Out

### Note:

- When plugin the fpc programming cable to DFRobot FPC programmer and cheapDuino, please the blue side facing upward.

### Example Code

- Choose the right com port of your programmer in the Arduino IDE first.
- Choose "Arduino NG or older /w ATmega8" in the "Boards" option.
- Then just upload your arduino sketch to the cheapDuino. The "Blink" sketch will be used to drive the LED connected to the D13 pin onboard.

```
const int ledPin = 13;          // the number of the LED pin on the cheapDuino

// Variables will change:
int ledState = LOW;              // ledState used to set the LED
long previousMillis = 0;         // will store last time LED was updated

// the follow variables is a long because the time, measured in milliseconds,
```

```

// will quickly become a bigger number than can be stored in an int.
long interval = 1000;           // interval at which to blink (milliseconds)

void setup() {
    // set the digital pin as output:
    pinMode(ledPin, OUTPUT);
}

void loop()
{
    // here is where you'd put code that needs to be running all the time.

    // check to see if it's time to blink the LED; that is, if the
    // difference between the current time and last time you blinked
    // the LED is bigger than the interval at which you want to
    // blink the LED.
    unsigned long currentMillis = millis();

    if(currentMillis - previousMillis > interval) {
        // save the last time you blinked the LED
        previousMillis = currentMillis;

        // if the LED is off turn it on and vice-versa:
        if (ledState == LOW)
            ledState = HIGH;
        else
            ledState = LOW;

        // set the LED with the ledState of the variable:
        digitalWrite(ledPin, ledState);
    }
}

```