

AC Power Supply - 12VDC,  
extended temp. NEMA 5-15P (US)  
to 2.1mm locking barrel plug.  
Compatibility: Digi TransPort  
WR41 (locking power cord  
models), Digi Connect WAN, Digi  
Connect WAN 3G, ConnectPort  
WAN, PortServer TS H, Digi  
TransPort WR21.

PART NUMBER:  
76000752

**Input Specifications:**

- Rated input voltage rating: 100VAC to 240VAC
- Input frequency: 47 Hz to 63 Hz

- Rated input current: 0.4A (rms) max. for 115VAC, 0.2 A (rms) max. for 230VAC
- Max. in-rush current: 25A MAX. @ 115VAC, 50A max. @ 230VAC at 25° C ambient cold start.
- Input Plug Type: NEMA 5-15P (NA)
- Leakage current: 1.0 mA max @230Vac.

**Output Specifications:**

- Output Voltage: 12VDC
- Load current: 1.0A
- Output Plug: 9.5 x 5.5 x 2.1mm locking barrel plug
- Max. output power: 12 watts continuous

**Environment:**

- Operating Temperature: -35° C to 74° C
- Storage Temperature: -35° C to 85° C

**Dimensions:**

- Size: 93 x 57 x 34mm
- Cord Length: 10ft

**Approvals:**

- Certifications: UL, cUL, CE