


Features

- Ideal for Printed Circuit Board
- Surge Overload Rating of 125A Peak
- Low forward Voltage Drop
- The Plastic Material Carries U/L Recognition 94V-0
- **Lead Free Finish, RoHS Compliant (Date Code 0514+) (Note 1)**

Mechanical Data

- Case: PB-6, Plastic
- Terminals: Leads Solderable per MIL-STD-202, Method 208
- Polarity: Symbols Marked on Body
- Weight: 4.56 grams



PB-6		
Dim	Min	Max
A	14.73	15.75
B	5.84	6.86
C	19	—
D	1.0 Typical	
E	1.7	2.7
G	3.6Ø	4.0Ø
H	10.3	11.3
All Dimensions in mm		

Maximum Ratings and Electrical Characteristics

Ratings at 25° C ambient temperature unless otherwise specified.
Single phase, 60Hz, resistive or inductive load.

Characteristic	Symbol	PB605	PB61	PB62	PB64	PB66	PB68	PB610	Unit
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Bridge Input Voltage	V_{RSM}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Output Current @ T_{HS} (Heatsink Temp) = 50°C	$I_{(AV)}$	6.0							A
Peak Forward Surge Current, 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	125							A
Maximum Forward Voltage Drop per element at 3.0Adc	V_F	1.1							V
Maximum dc Reverse Current at rated dc Blocking Voltage per element @ $T_A = 25^\circ\text{C}$ @ $T_A = 100^\circ\text{C}$	I_R	10 1							μA mA
Typical Thermal Resistance	R_{JC}	8							°C/W
Operating and Storage Temperature Range	T_J, T_{STG}	-65 to +150							°C

Notes: 1. EC Directive 2002/95/EC (RoHS) revision 13.2.2003. Glass and High Temperature Solder Exemptions Applied where applicable, see *EU Directive Annex Notes 5 and 7*.




Fig. 1, Derating Curve for Output Rectified Current




Fig. 2, Typical Forward Characteristics




Fig. 3, Maximum Forward Surge Current




Fig. 4, Typical Reverse Characteristics

**NOT RECOMMENDED FOR NEW DESIGNS -
USE PBPC601-PBPC607**

Ordering Information (Note 2)

Device	Packaging	Shipping
PB605	PB-6	200 Bulk
PB61	PB-6	200 Bulk
PB62	PB-6	200 Bulk
PB64	PB-6	200 Bulk
PB66	PB-6	200 Bulk
PB68	PB-6	200 Bulk
PB610	PB-6	200 Bulk

Notes: 2. For Packaging Details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

IMPORTANT NOTICE

Diodes, Inc. and its subsidiaries reserve the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. Diodes, Inc. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

The products located on our website at www.diodes.com are not recommended for use in life support systems where a failure or malfunction of the component may directly threaten life or cause injury without the expressed written approval of Diodes Incorporated.

**NOT RECOMMENDED FOR NEW DESIGNS -
USE PBPC601-PBPC607**