## **SERIES EG1400 SWITCHES**



## SLIDE SWITCHES



FEATURES & BENEFITS Tape & Reel Packaging 3-position Sub-miniature Surface Mount


APPLICATIONS / MARKETS Computer Servers/peripherals Consumer electronics Instrumentation Test & measurement


Nechanical Life:	10,000 cycles	
Force:	200 +/- 150 gf in both directions	
Travel:	1.5 +/- 0.1mm each position	
ELECTRICAL SPECIFI	CATIONS	
Electrical Life:	10,000 cycles	
Contact Rating:	300mA @ 4VDC	
Contact Resistance:	70m $\Omega$ (initial max)	
Insulation Resistance:	100MΩ (Min @ 100VDC)	
Dielectric Strength:	100VAC	
ENVIRONMENTAL SP	ECIFICATIONS	
Operating Temperature:	-10°C to +60°C	
Storage Temperature:	-20°C to +80°C	


HOW TO ORDER:


SERIES	MODEL	ACTUATOR
EG		
	1400	A = 1.00mm B = 2.50mm











7153 NORTHLAND DRIVE NORTH MINNEAPOLIS, MN 55428 PHONE: 800-867-2717 FAX: 763-531-8235

www.e-switch.com email: info@e-switch.com