

# AMG SERIES



## BOLT IN AUTOMOTIVE FUSES

### SPECIFICATIONS:

**Applications:** For high current applications. Use with Bussmann HMG or FMG fuseholders. (See pages 12-13.)

**Current Rating:** 100-300A.

**Voltage Rating:** 32VDC.\*

**Interrupt Rating:** 1,000A @ 32VDC.

**Housing Material:** UL-Rated 94V-0 thermoplastic.

**Terminal Material:** Copper.

**Mounting:** M8 or 5/16-18 or less studs on 2.00 in (50.8mm) centers.

**Marking:** Color-coded amperage ratings.

\*Consult factory for higher voltage fuses.

### TIME-CURRENT SPECIFICATIONS

% of Rating	Opening Time	
	Minimum	Maximum
100	100 hrs	
135	120 s	1800 s
200	1 s	30 s
350	0.1 s	5 s
600	0.02 s	1 s

### PART NUMBERING SYSTEM

#### Series

B K / A M G — □ □ □

#### Rating

100 – 100 amps  
125 – 125 amps  
150 – 150 amps  
175 – 175 amps  
200 – 200 amps  
225 – 225 amps  
250 – 250 amps  
300 – 300 amps

### DIMENSIONS (Dims. are shown for reference only. Consult factory for latest prints)

