

**ebm-papst Mulfingen GmbH & Co. KG**

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.ebmpapst.com

www.ebmpapst.com

Limited partnership · Headquarters Mulfingen

County court Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

County court Stuttgart · HRB 590142

**Nominal data**

|                               |                       |         |         |
|-------------------------------|-----------------------|---------|---------|
| <b>Type</b>                   | <b>W2E142-BB01-01</b> |         |         |
| <b>Motor</b>                  | <b>M2E052-BA</b>      |         |         |
| Phase                         |                       | 1~      | 1~      |
| Nominal voltage               | VAC                   | 230     | 230     |
| Frequency                     | Hz                    | 50      | 60      |
| Type of data definition       |                       | fa      | fa      |
| Valid for approval / standard |                       | CE      | CE      |
| Speed                         | min <sup>-1</sup>     | 2800    | 3350    |
| Power input                   | W                     | 27      | 28      |
| Current draw                  | A                     | 0.12    | 0.13    |
| Motor capacitor               | µF                    | 1       | 1       |
| Capacitor voltage             | VDB                   | 400     | 400     |
| Capacitor standard            |                       | P0 (CE) | P0 (CE) |
| Min. ambient temperature      | °C                    | -25     | -25     |
| Max. ambient temperature      | °C                    | 55      | 65      |


ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit  
Subject to alterations



### Technical features


|   |   |
|---|---|
| <b>Mass</b>   | 0.8 kg  |
| <b>Size</b>   | 142 mm  |
| <b>Surface of rotor</b>   | Coated in black                                   |
| <b>Material of impeller</b>   | Sheet steel, coated in black                      |
| <b>Material of wall ring</b>  | Die-cast aluminium, coated in black               |
| <b>Number of blades</b>   | 7   |
| <b>Direction of air flow</b>  | "V"   |
| <b>Direction of rotation</b>  | Counter-clockwise, seen on rotor                  |
| <b>Type of protection</b>   | IP 22; Depending on installation and position     |
| <b>Insulation class</b>   | "B"   |
| <b>Max. permissible ambient motor temp. (transp./ storage)</b>            | + 80 °C   |
| <b>Min. permissible ambient motor temp. (transp./storage)</b>             | - 40 °C   |
| <b>Mounting position</b>  | Any   |
| <b>Condensate discharge holes</b>   | None  |
| <b>Operation mode</b>   | S1  |
| <b>Motor bearing</b>  | Ball bearing                                      |
| <b>Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)</b> | < 0.75 mA   |
| <b>Electrical leads</b>   | With plug   |
| <b>Motor protection</b>   | Thermal overload protector (TOP) wired internally |
| <b>Protection class</b>   | I (if earth wire is connected by customer)        |
| <b>Product conforming to standard</b>                                     | EN 60335-1; CE                                    |
| <b>Approval</b>   | CCC; CSA C22.2 Nr.113; EAC; UL 507; VDE           |

## Product drawing




1 2x flat plug 2.8 x 0.5 mm

## Connection screen



## Charts: Air flow 50 Hz



Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.


## Measured values

|   | U   | f  | n                 | P <sub>e</sub> | I    | qv                | P <sub>fs</sub> |
|---|-----|----|-------------------|----------------|------|-------------------|-----------------|
|   | V   | Hz | min <sup>-1</sup> | W              | A    | m <sup>3</sup> /h | Pa              |
| 1 | 230 | 50 | 2800              | 27             | 0.12 | 320               | 0               |
| 2 | 230 | 50 | 2800              | 27             | 0.12 | 300               | 17              |
| 3 | 230 | 50 | 2795              | 27             | 0.12 | 275               | 33              |
| 4 | 230 | 50 | 2775              | 27             | 0.12 | 240               | 50              |

U = Supply voltage · f = Frequency · n = Speed · P<sub>e</sub> = Power input · I = Current draw · qv = Air flow · P<sub>fs</sub> = Pressure increase



## Charts: Air flow 60 Hz



Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: L<sub>WA</sub> measured as per ISO 13347 / L<sub>pA</sub> measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

## Measured values

|   | U   | f  | n                 | P <sub>e</sub> | I    | qv   | P <sub>fs</sub> |
|---|-----|----|-------------------|----------------|------|------|-----------------|
|   | V   | Hz | min <sup>-1</sup> | W              | A    | m³/h | Pa              |
| 1 | 230 | 60 | 3350              | 28             | 0.13 | 385  | 0               |
| 2 | 230 | 60 | 3310              | 29             | 0.13 | 355  | 23              |
| 3 | 230 | 60 | 3270              | 30             | 0.13 | 320  | 47              |
| 4 | 230 | 60 | 3230              | 31             | 0.14 | 270  | 70              |

U = Supply voltage · f = Frequency · n = Speed · P<sub>e</sub> = Power input · I = Current draw · qv = Air flow · P<sub>fs</sub> = Pressure increase

