

About Us

Products

Services

Support

Projects

Web Shop

Products

- > Board Comparison Chart
- » Developer's Kits
- » OEM Boards
- » QuickStart Boards
- » Education Boards
- ↓ LPCXpresso & mbed
- > LPCXpresso LPC1114
- > LPCXpresso LPC11U14
- > LPCXpresso LPC11C24
- > LPCXpresso LPC1227
- > LPCXpresso LPC1343
- > LPCXpresso LPC1769
- > LPCXpresso Prototype
- > LPCXpresso Base
- > LPCXpresso Value Pack
- > LPCXpresso Motor Control
- > mbed
- » Displays
- » Tools
- » Accessories

LPC11U14 LPCXpresso Board



Picture not showing correct version of LPCXpresso board.

The LPC11U14 LPCXpresso board with NXP's ARM Cortex-M0 microcontroller has been designed to make it as easy as possible to get started with Cortex-MO. The LPCXpresso comprises a target board combined with a JTAG debugger. A free Eclipsebased IDE from Code Red is also included.

The LPC11U14 has 6 kB SRAM, 32 kB Flash, USB 2.0 Full-Speed Device, SSP, I2C, UART, ADC, etc. Embedded Artists also provides a Prototype board and a Base board that makes it possible to make experiments and prototyping with many peripherals.

Embedded Artists and Code Red offer LPCXpresso customers valuable discounts. Embedded Artists gives 15 EUR discount on the regular Developer's kits and 7 EUR off the LPCXpresso Base board. Code Red has an offer to upgrade to full-blown suites. For more information see LPCXpresso discount.

Price Information

EUR

Art.no: EA-XPR-007 Buy

Currently out-of-stock

Expected delivery date: 2011-07-30

Price Information

EUR

LPCXpresso Kit containing LPC11U14 and <u>Base Board</u>

Art.no: EA-XPR-107 Buy

Currently out-of-stock

Expected delivery date: 2011-07-30

Overview Specification MCU **Related Products** Resources FAQ

LPC11U14 LPCXpresso Board

Processor

NXP's Cortex-M0 LPC11U14 microcontroller in LQFP48 package

Flash

32 kB

Data Memory

6 kB 12.000 MHz crystal for CPU

Clock Crystals Dimensions

35 x 140 mm

Power

3.15V-3.3V external powering, or from USB via JTAG probe (LPC-LINK)

Connectors

• mini-B USB connector for LPC11U14 USB interface

• All LPC11U14 pins available on expansion connector (2x27 pin rows, 100 mil pitch, 900 mil between rows)

Other

• Embedded JTAG (LPC-LINK) functionality via LPCXpresso toolchain

• LPC-LINK can be connected to external target processor after modifications to the LPCXpresso board

• LED on PIOO_7

© Embedded Artists Legal Information Privacy Statement The Art of Embedded Systems Development - made Easy ™