

Part No. 9000984-XLPDNB

External NB-IoT/LoRa/Sigfox Antenna

790-960MHz



Ethertronics' series of External Antennas deliver on the key needs of device designers for higher functionality and performance in access points. Small form factor and wall mount fixture, ideal to offer outdoor areas coverage.

Extensive RF Experience

Our external antennas are supported by documentation, and when needed, by the expertise of RF engineers who have integrated hundreds of antenna designs into wireless devices.

Global Operations & Design Support

Ethertronics' global operations encompass an integrated network of design centers that provide local customer support.

External NB-IoT/LoRa/Sigfox Antenna

790/960 MHz

KEY BENEFITS

Quicker Time-to-Market

Standard part means fewer design changes
 Simple implementation
 Easy Assembly using RP-SMA or SMA

Best in Class Performance

External antennas are designed to maintain high efficiency in a variety of device configurations

Superior Network Coverage

Better network coverage means more reliable wireless connections

Great Flexibility

Standard connector makes for easy set-up

APPLICATIONS

- Gateways
- Metering
- IoT devices
- TVs

Electrical Specifications

Typical Characteristics in Free Space and on a connected to a 200x200mm ground plane and under PC/ABS plastic cover

| Frequency bands | Free Space | | | 200x250mm PCB | | |
|------------------------|-----------------|--------|--------|---------------|--------|--------|
| | 790MHz | 868MHz | 915MHz | 790MHz | 868MHz | 915MHz |
| Return loss (dB) | <-4 | <-17 | <-9 | <-4 | <-13 | <-13 |
| Efficiency (%) | 40 | 85 | 75 | 40 | 80 | 82 |
| Peak Gain (dBi) | 2.2 | | | 3.4 | | |
| Impedance (Ω) | 50 | | | | | |
| Working Temperature | -40°C to +120°C | | | | | |

Mechanical Specifications


| | |
|------------|---|
| Dimensions | 195 mm x 12.98 mm |
| Connector | SMA Male (RP-SMA available upon request) |
| Hinge | Foldable 90 degrees at the hinge level |
| Color | Black (other colors available upon request) |



External NB-IoT/LoRa/Sigfox antenna specifications
Ethertronics produces a wide variety of standard and custom antennas to meet user needs.
Below are the typical performances


Return loss

Typical Characteristics (measurements taken in Free Space and on a 200 x 200 mm ground plane)



Efficiency

Typical Characteristics (measurements taken in Free Space and on a 200 x 200 mm ground plane)



*All dimensions provided in this document are for informational purposes only




External NB-IoT/LoRa/Sigfox antenna specifications
Ethertronics produces a wide variety of standard and custom antennas to meet user needs.
Below are the typical performances


Radiation pattern

Typical Characteristics (measurements taken in Free Space and on a 200 x 200 mm ground plane)

- At 790MHz



- At 850MHz



- At 950MHz

