

Quick Charger Specification (FCT344)

FDK

Compatible cells		AA / AAA (1 ~ 4 cells), Individual charging	
Input Voltage		AC 100-240V, 50-60Hz	
Charge Current		AA: 1100mA (1~2cells),	550mA (3~4cells)
		AAA: 560mA (1~2cells),	280mA (3~4cells)
Charge Time		1~2 cells	3~4 cells
	AA (min.1900mAh)	Approx. 2 hrs	Approx. 4 hrs
	AAA (min.750mAh)	Approx. 1.5 hrs	Approx. 3 hrs
Charge Control		-ΔV, Timer	
LED Indicator		Charging: Turn On; Fully charging: Turn Off; Abnormal: Flashing	
Safety function		High temperature detection, Timer, Over-discharge cell detection, Reverse polarity charging prevention, Primary cell & End-of-Life cell detection	
Temperature range		0°C~35°C (Operating), -20°C~60°C (Storage)	
Safety approval		PSE (Japan), CE (Europe), ETL (USA), BSMI (Taiwan), SAA (Australia), KC (South Korea), BS (UK), EAC (Russia)	
Dimensions / Weight		108(L) x 68(W) x 28(H)mm / Approx. 100g	
Others		A plug [Japan, USA, Taiwan, Thailand, China], SE plug [South Korea], C plug [Europe, SP, Russia], BF plug [UK, HK, SP], O plug [Australia]	