

Product SKU:	C1302.41.01
Product Description:	Microphone Cable, Multi-Conductor, Braid Shield, No. of Conductors: 2, Gauge Size (AWG): 20, Conductor/Strands: 26/34, Jacket: Black Rubber, Temperature Range: -20Â°C to +60Â°C - Black - 1000 Ft. Reel
Product Category:	Electronics - Microphone Cable - Braid Shield Rubber Jacket - Black

**Product Construction:**

Conductor:	<ul style="list-style-type: none">• 20 AWG fully-annealed, solid tinned copper per ASTM B-33
Insulation:	<ul style="list-style-type: none">• Color Code: See chart below• Premium grade color coded rubber
Shield:	<ul style="list-style-type: none">• 80% tinned copper braid
Jacket:	<ul style="list-style-type: none">• Rubber, black• Temperature Range: -20Â°C to +60Â°C

Product Specification:

No. of Conductors:	<ul style="list-style-type: none">• 2
Conductor Size (AWG):	<ul style="list-style-type: none">• 20
Conductor/Strands:	<ul style="list-style-type: none">• 26/34
Jacket Color:	<ul style="list-style-type: none">• Black
Nominal Insulation Thickness (in):	<ul style="list-style-type: none">• 0.020
Nominal Insulation Thickness (mm):	<ul style="list-style-type: none">• 0.51
Nominal Jacket Thickness (in):	<ul style="list-style-type: none">• 0.035
Nominal Jacket Thickness (mm):	<ul style="list-style-type: none">• 0.89

Nominal Outside Diameter (in):	<ul style="list-style-type: none">0.270
Nominal Outside Diameter (mm):	<ul style="list-style-type: none">6.86
Standard Packaging:	<ul style="list-style-type: none">1000' Non-returnable Wood Reels
Standard Package Quantity:	<ul style="list-style-type: none">1
UPC #:	<ul style="list-style-type: none">079407713301
Put-up:	<ul style="list-style-type: none">1000
SCC-14:	<ul style="list-style-type: none">50079407713300
Cube:	<ul style="list-style-type: none">2332.8
Weight Per Unit of Measure:	<ul style="list-style-type: none">.05
ColorOption:	<ul style="list-style-type: none">Black

Product Information:

Applications:	<ul style="list-style-type: none">Audio interconnectsBroadcast and studio applicationsControl circuitsSuggested voltage rating: 300 Volts
Features:	<ul style="list-style-type: none">Impact and abrasion resistantStranded conductors for superior flexibility
Packaging:	<ul style="list-style-type: none">1000' (305 m) Spools or Reels500' (152 m) Spools or ReelsOther put-ups available- consult Customer ServiceMinimum runs may apply - consult customer service

Reference Charts

[Color Code Chart](#)

Technical Specifications

[Unit Conversion Factors](#)

[Cable Design Equations - Balanced Pair](#)

[Insulation and Jacket Properties](#)

[Temperature Conversion Chart](#)

[Decimal and Unit Conversion Factors](#)

[Cable Design Equations - Braid Shield](#)

[AWG Conductor Chart](#)

[Conduit Capacity Chart](#)

[Cable Design Equations - Coaxial Cable](#)

[Engineering Prefixes](#)

[Coax Connector Cross Reference](#)

[Glossary](#)

**CAROL
BRAND**