



SERIES 90B Machine Insertable MIDIP




FEATURES

- Tested for TO-116 Equipment
- Up to 10 Positions
- High Pressure, Reliable Contacts
- Molded (Sealed) Base and Optional Top Seal




DIMENSIONS In inches (and millimeters)



CIRCUITRY

As viewed from the top of the switch in the positions shown in the drawing.



ORDERING INFORMATION: Tube Packaging (Each tube is 19.5 inches long)

No. of Positions	Length Inches	Length Metric	Number Per Tube	Part Number*
2	.270"	6,9 mm	60	90B02S
3	.370"	9,4 mm	47	90B03S
4	.470"	11,9 mm	37	90B04S
5	.570"	14,5 mm	31	90B05S
6	.670"	17,0 mm	26	90B06S
7	.770"	19,6 mm	23	90B07S
8	.870"	22,1 mm	20	90B08S
9	.970"	24,6 mm	18	90B09S
10	1.070"	27,2 mm	16	90B10S

*The "S" at the end of the part number denotes top tape seal versions. To order without top tape seal, leave the "S" off the part number when ordering.

ADDITIONAL INFORMATION

For Specifications, see page B-14.
For Options and Accessories, see page B-20.

Available from your local Grayhill Distributor.
For prices and discounts, contact a local Sales Office, an authorized local Distributor or Grayhill.