

1-Piece Fixing Ties with Arrowhead, with Disc in the strap T50RSP



Article number: 150-35930

- Arrowhead located on strap for minimal space
- Disc covering hole for reduced ingress of water and dirt
- Flexible discs for firm but secure fixing of any panel thickness
- Tab on end to facilitate easy location and orientation of head for assembly

With a diverse range of fixing possibilities (from 5.7mm to 6.5mm hole diameters and 0.7mm to 3.5mm panel thickness) this range of fixing ties is ideal for use in many different industries, including automotive, aerospace and panel building.


[Catalogue page \(April 2011\)](#)

[All catalogue pages](#)

[Print](#)

Base Data

Application Tool	MK20, MK3PNSP2, MK3SP, MK7P, MK7
Colour	Black (BK)
Fixation Method (FF)	Arrowhead
Identification Plate Position	none
Product Group	1-Piece Fixing Ties with Arrowhead, with Disc in the strap
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Type	T50RSP.NB7P
Variant	Inside Serrated

Product Dimensions

Bundle Ø max.	45.0 mm
Bundle Ø min.	7.0 mm
Disc Ø	18.0 mm
Disc Ø (imperial)	0.71 "
Fixing Hole Diameter D max (Imperial)	0.26 "
Fixing Hole Diameter D min (Imperial)	0.24 "
Hole Ø	6.4 mm
Hole Ø (FH)	6.0 - 6.5 mm
Hole Ø (FH) min.	6 mm
Length (L)	190 mm
Length (L) (imperial)	7.48 "
Min. Tensile Strength (lbs)	50 lbs
Min.Tensile Strength (N)	225 N
Panel Thickness max.	1.3 mm
Panel Thickness max. (imperial)	0.05 "
Panel Thickness min.	0.75 mm
Panel Thickness min. (imperial)	0.03 "
Thickness (T)	1.2 mm
Width (W)	4.6 mm
Width (W) (imperial)	0.18 "

Logisitic and Packaging

Carton Quantity	8000 pcs.
EAN code	4031026120522
Pack Cont.	1000

Quantity of Europallet	96000 pcs.
Quantity per	Bag
UPC	089306207375
Weight	1.5 kg
Material and Specifications	
Flammability	UL94 V2
Material	PA66
Material	Polyamide 6.6 (PA66)
Operating Temperature	-40 °C to +85 °C
More Information	
UNSPSC Key	39121717