

Home

Events

Careers

How To Buy

Contact

HellermannTyton

Products

Industries

Resources

News

About Us

▶ Cable Ties

▶ Cable Ties with Fasteners

▶ Cable Tie Tools

▶ Clamps and Clips

▶ Heatshrink Moulded Shapes

▶ Mounts

▶ Heavy Duty Mounts

▶ Wire Connectors

▶ Wiring Duct

▶ Wiring Protection

▶ Labels, Printers and Software

▶ Pre-Terminated Networking

▶ Copper Network Solutions

▶ Fiber Network Solutions

▶ Jacks and Wall Plates

▶ Racks - Cable Management

▶ Surface Raceway Systems

T30L0UVC2

Standard Cable Tie, 7.8" Long, 30lb Tensile Strength, PA66UV, Black, 100/pkg

Article Number: 111-00437

Part Number: T30L0UVC2

Type: T30L

➔Find a Distributor

➔Order Samples

➔Get Technical Drawings

Share

➔Base Data

Part No.	T30L0UVC2
Type	T30L
Color	Black (BK)
Features	• UV stabilized cable ties contain an inhibitor which prolongs the life of the tie in UV exposures . • Inside serrations allow for strong hold on cables and wire bundles. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
Application Method	Quick, simple fixing by hand or with HellermannTyton tensioning tools
Identification Plate Position	none
Releasable Closure (Yes / No)	No
Tie Closure	plastic pawl
Typical Application	Used to bundle and secure wire and cable.
Variant	Inside Serrated

➔Product Dimensions

Min. Tensile Strength	30.0lbs / 135.0N
Length (L)	198.0mm
Width (W)	3.6mm
Min. Ø Bundle	1.5mm
Max. Ø Bundle	50.0mm

➔Material and Specifications

Material	Polyamide 6.6 UV-resistant (PA66UV)
Flammability	UL94 V2
Material Specification	HF / RoHS
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity	✓ RoHS
Specification	UL ZODZ2.E64139
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	No

http://www.hellermannntyton.us/productDetail.aspx?lon=T30L0UVC2&ref=search.aspx[11/8/2013 1:48:09 PM]

 Logistic and Packaging

Packaging Type	bag
Pkg. Qty.	100
UPC	089306272588

[Find a Distributor](#)

[Get Product Samples](#)

[Get Technical Drawings](#)