

Products

www.hellermannntyton.co.uk | Products | Identification Systems | Wire and Cable Markers

About Us

Products

Product highlights

Product overview

Cable Ties and Fixings (1668)

Insulation Products (2244)

Cable Protection Systems (1683)

Installation Devices (197)

Identification Systems (2438)

Control Panel Labelling (68)

Industrial Identification (310)

Security Labeling (156)

Hazardous Area Identification (85)

Printers and Software (43)

Application Tooling (134)

Connectivity (1207)

T.I.P.S.

Project Management-Autotool- Automatic Cable Tying Systems

Competences

Career

News & Events

Downloads

TAGH27



These labels are particularly suitable for permanent identification on flat surfaces for production equipment or IT devices. Using unique numbering, graphics, or barcodes the labels give excellent asset identification possibilities. The extensive range has sizes to suit most needs.

For Flat Surfaces Only

Print

UPC	089306225836
Weight	0.3 kg
▼	
Adhesive	Acrylic
Adhesive Operating Temperature	-40 °C to +150 °C
Chem. Material Properties	Resistant to most chemicals and solvents
Curing Temperature	from +10 °C
Material	799
Material	Type 799, Polyester, silver matt (SR)
Mech. Material Properties	Durable polyester
Operating Temperature	-40 °C to +150 °C
Shortcut Adhesive	Acryl
Specification	UL -Recognised
UL OCD link	Link Link
UL -File Number	MH18396
▼	
UNSPSC Key	39131504