Honeywell

Honeywell Sensing and Control

Home> Products > Piezoresistive Silicon > 236PC> Product Page

Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback



Pressure Sensors: Measurement Type: Gage, Vacuum Gage; Unamplified; Range: ±60.0 psi

Potential Applications

Medical

Robust package Prewired Temperature compensated for span over 0 °C to 50 °C [32 °F to 122 °F] Calibrated null and span

Oxygen and nitrogen gas distribution in hospitals Respirators and ventilators **Environmental** Water control valves Instrumentation Irrigation equipment **Industrial Instrumentation** Robotics Pressure valves Leak detection Air compressors Login as Rep/AD Login as Guest Login to Digital University Keyword Search Search for product and support information. All Sensing and Contre Product Search Part number search:

My Links

Login to iCOM

Use (*) to expand search

Specification Search

Description

Features

236PC Series pressure sensors provide a millivolt output that is proportional to the pressure applied. They operate from 0 psi to 5.0 psi and 0 psi to 150 psi using a single, positive supply voltage ranging from 10.0 Vdc to 16.0 Vdc.

Supporting Documentation

Engineering Drawing

Product Specifications	
Signal Conditioning	Unamplified
Pressure Range	± 60.0 psi
Maximum Overpressure	100 psi
Supply Voltage	10 Vdc typ., 16.0 Vdc max.
Compensated	No
Output Calibration	Yes
Response Time	1 ms max.
Port Style	Threaded 1/4 - 28 UNF
Package Style	Honeywell - 200PC
Typical Sensitivity	1.0 mV/psi
Full Scale Span	60 mVdc typ.
Null Offset	0 mV typ.
Null Shift over Temperature	± 3.0 mV typ.
Repeatability & Hysteresis Error	± 0.25 % span typ.
Shock	Qualification tested to 150 g
Vibration	MIL - STD - 202 Method 213 (150 g half sine 11 ms)
Weight	57 g [2 oz]
Operating Temperature Range	- 30 °C to 70 °C [-22 °F to 1581 ° F]
Compensated Temperature Range	0 °C to 50 °C [32 °F to 122 °F]
Storage Temperature Range	- 40 °C to 105 °C [- 40 °F to 221 ° F]
UNSPSC Code	411121
UNSPSC Commodity	411121 Transducers
Availability	Global
Series Name	236PC

Terms & Conditions | Privacy Statement | Site Map