

PART NUMBER SEE SHEET-2 TABLE **CHARACTERISTICS** MARKING / **ELECTRICAL MECHANICAL LISTING** В D $\operatorname{RES}(\Omega)$ SHAFT SLOT RES SLOT BUSHING MTG LINE-I LINE-2 LINE-3 LINE-4 TOL DEPTH WIDTH LENGTH LENGTH HARDWARE IN [mm] IN [mm] IN [mm] IN [mm] .625 . 250 .031 UNASSEMBLED 392550M6965 IOK Ω RV6NAYSAI03A IOK Ω MEXICO ±10% 20 YYWW [0.79] [0.79] [15.88] [6.35] . 625 .031 .031 . 250 5Κ Ω 5Κ Ω 392550M9277 ±10% UNASSEMBLED RV6NAYSA502A MEXICO 20 YYWW [0.79] [0.79] [15.88] [6.35] .625 .031 .031 . 250 50k Ω 392550M9392 50K Ω UNASSEMBLED RV6NAYSA503A ±10% 20 YYWW MEXICO [0.79] [0.79] [15.88] [6.35] . 500 .031 .031 . 250 Ω 001 UNASSEMBLED Ω 001 392550M9510 ±10% RV6NAYSBIOIA 20 YYWW MEXICO [0.79] [0.79] [12.70] [6.35] . 500 .031 . 250 .031 20 YYWW 392550M7183 $10 \mathrm{K}\Omega$ ±10% UNASSEMBLED RV6NAYSB103A 10K Ω MEXICO [0.79] [12.70] [0.79] [6.35] .500 .031 . 250 .031 5Κ Ω 5Κ Ω 392550M9618 ±10% UNASSEMBLED RV6NAYSB502A 20 YYWW MEXICO [0.79] [0.79] [12.70] [6.35] .875 .031 . 250 .031 Ω 001 ASSEMBLED RV6NAYSDIOIA 392C3 100ΩMEXICO 392C3100 ±10% 20 YYWW [0.79] [0.79] [22.23] [6.35] . 875 .031 .031 . 250 I K Ω 392C3 ΙKΩ 392C31K ±10% ASSEMBLED RV6NAYSD102A 20 YYWW MEXICO [0.79] [22.23] [0.79] [6.35] . 875 .031 .031 . 250 IOK Ω 20 YYWW 392C3I0K ASSEMBLED RV6NAYSDI03A 392C3 10K Ω MEXICO ±10% [0.79] [22.23] [6.35] [0.79] .031 .031 . 875 . 250 392C3I00K 100K Ω **ASSEMBLED** RV6NAYSDI04A 392C3 IOOK Ω 20 YYWW MEXICO ±10% [22.23] [0.79] [0.79] [6.35] .031 .031 .875 . 250 IMEG Ω ±10% 392C3IMEG ASSEMBLED RV6NAYSDI05A 392C3 IMEG Ω 20 YYWW MEXICO [6.35] [22.23] [0.79] [0.79] .031 .031 .875 . 250 ±10% 250Ω 392C3 250Ω392C3250 ASSEMBLED RV6NAYSD251A 20 YYWW MEXICO [0.79] [0.79] [22.23] [6.35] . 875 .031 .031 . 250 392C32500 2.5K Ω ±10% ASSEMBLED RV6NAYSD252A 392C3 2.5K Ω 20 YYWW MEXICO [6.35] [0.79] [22.23] [0.79] .875 .031 . 250 392C325K 25K Ω ±10% ASSEMBLED RV6NAYSD253A $392C3 25K\Omega$ 20 YYWW MEXICO [0.79] [0.79] [22.23] [6.35] .031 .031 . 875 . 250 250K Ω ASSEMBLED RV6NAYSD254A 392C3 250 kΩ 392C3250K ±10% 20 YYWW MEXICO [0.79] [0.79] [22.23] [6.35] .031 .031 . 875 . 250 500Ω ASSEMBLED 392C3 500Ω392C3500 ±10% RV6NAYSD501A 20 YYWW MEXICO [0.79] [0.79] [22.23] [6.35] . 875 .031 .031 . 250 5K Ω 392C3 5K Ω 392C35K ±10% ASSEMBLED RV6NAYSD502A 20 YYWW MEXICO [0.79] [0.79] [22.23] [6.35] .875 .031 .031 . 250 5Κ Ω 5Κ Ω 392550M9627 $\pm 20%$ UNASSEMBLED RV6NAYSD502B 20 YYWW MEXICO [22.23] [0.79] [0.79] [6.35] .875 .031 .031 . 250 50K Ω 392C350K ±10% ASSEMBLED RV6NAYSD503A 392C3 50 kΩ MEXICO 20 YYWW [0.79] [0.79] [22.23] [6.35] . 875 .031 .031 . 250 500KΩ 392C3 500 kΩ MEXICO 392C3500K ±10% ASSEMBLED RV6NAYSD504A 20 YYWW [0.79] [22.23] [0.79] [6.35] . 375 . 250 .031 10K Ω 392C4I0K ±10% ASSEMBLED RV6NAYSL103A 392C4 10K Ω 20 YYWW MEXICO [0.79] [0.79] [9.53] [6.35] . 375 .031 .031 . 250 20 YYWW 100K Ω ASSEMBLED RV6NAYSLI04A 392C4 IOOK Ω MEXICO 392C4I00K ±10% [0.79] [9.53] [0.79] [6.35] .031 . 375 . 250 ASSEMBLED 500K Ω ±10% 392C4 500 kΩ 20 YYWW 392C4500K RV6NAYSL504A MEXICO [6.35] [0.79] [0.79][9.53] . 875 . 250 .031 .031 Ω 001 ASSEMBLED RV6SAYSDIOIAP 392C5 100 Ω 392C5100 20 YYWW MEXICO [0.79] [0.79] [22.23] [6.35] Honeywell S-TAPER, SLOTTED SHAFT, STD BUSHING, SOLDER HOOK TERMS SIZE CAGE CODE DWG NO 392-MATRIX-IDWG-15 REF WT: SEE NOTE SHEET 2 of 2 SCALE NONE