

## Honeywell Sensing and Control



Home > Products > Conductive Plastic Potentiometers > 381 > Product Page

### D381N10K



Actual product appearance may vary.

**381 Series Industrial Potentiometer, Conductive Plastic Element, Solder lug Terminals, 1 W Power Rating, 10 kOhm Resistance Value**

#### ▼ Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

#### Features

Conductive plastic element  
Linear taper  
Rugged construction: Metal case and nickel-plated brass shaft and bushings  
Solder lug terminals  
Dual section controlled by one shaft

#### Potential Applications

Manual controls  
Welding and heating  
Telecommunications

#### Description

The 381 Series is a 1 watt potentiometer with a conductive plastic element and a metal housing.

#### Supporting Documentation

▣ [Dimensions](#)

▣ [Accessory: Knobs](#)

#### My Links

- [Login to iCOM](#)
- [Login as Rep/AD](#)
- [Login as Guest](#)
- [Login to Digital University](#)

#### Keyword Search

Search for product and support information.

 [→](#)

#### Product Search

Part number search:

 [→](#)  
 Use (\*) to expand search

→ [Specification Search](#)

#### Product Specifications

Potentiometer Type	Industrial
Element Type	Conductive Plastic
Terminal	Solder lug
Power Rating	1 W
Resistance Value	10 kOhm
Resistance Tolerance	± 10 %
Linearity	± 5 %
Bushing Thread	6,35 mm [0.25 in] x 32 NEF-2A
Bushing Length	6,35 mm [0.25 in]
Bushing Type	Standard
Shaft Diameter	3,18 mm [0.125 in]
Shaft Length	19,05 mm [0.75 in]
Shaft Ending	Slotted
Body	15.88 mm [0.625 in] diameter, ± 0.79 mm [0.031 in]

Electrical Taper	Linear
Operating Temperature	-40 °C to 120 °C [-40 °F to 248 °F]
Working Voltage (Max.)	350 V
Rotational Life	25000 cycles
Mechanical Rotation	300°
Availability	Global
Series Name	381
UNSPSC Code	4111363300
UNSPSC Commodity	4111363300 Potentiometers

[Terms & Conditions](#) | [Privacy Statement](#) | [Site Map](#)