Honeywell			→ Honey	well.com 🗦 Automation & C	ontrol Solation	
HOME ABOUT US	KEY INDUSTRIES SERVED	PRODUCTS & INFORMATION	NEWS & EVENTS	SALES & SUPPORT	LOGIN	
Honeywell Sensing a	nd Control					
Search Description narrow your search Products • Controls Monitoring and Lighting (352) • Machine Safety (1727) • Sensors (5898) • Switches (9774) • Wireless (99) Technology • Control and Instrumentation (1052) • Electromechanical (9300) • Microstructure (1491) • Optical/Infrared (1042) • Thick Film (1409) • More	Package * SD3491)	(Home : Products : Sensors » Infrared Sensors » Phototransistors - Metal Package » SD3491) SD3491 Series Silicon Phototransistor, TO-46 Metal, Flat Window Can		Customer Service Technical Suppor Global Sales & S View Site Demo Site Comments? VIDEO - Dr. Larry Goldstein explains our newest and bes	t ervice meet dr. larr	
	may vary.	Sales & Service 🥥 D	Distributor Inventory	etechnologies. Meet Dr. Larry	my link	
ew products	Overview Specs Docur	nentation Application Notes		Login to iCOM Login to Rep/AD	Portal	
New Wireless Products	Product Specifications			Login to Digital U	niversity	
o farther. Work smarter. Explore new ssibilities. Just by cutting the cord d making the switch.	Product Type	SD3491 IR Component			News Cent	
Propries of the Independent	Angular Response (Degree) Light Current Minimum Package Type Hermetic Style Rise and Fall Time	90 0.45 mA TO-46, Flat Window Yes 2 µs		ADDITION TO RI RESIDENTIAL D INTERLOCK SW	HONEYWELL ANNOUNCES ADDITION TO RELIALIGN™ RESIDENTIAL DOOR INTERLOCK SWITCHES THAT FEATURE RUGGED, PLASTIC HOUSING	
ireless Web Site GLA and WPMM /R6000™	Power Dissipation Operating Temperature Dark Current	250 mW -65 °C to 125 °C [-85 °F to 257 °F] 100 nA		HONEYWELL RE UNLIMITED POT NEW LIMITLESS SWITCHES	ENTIAL WITH	
find out more	Collector-Emitter Breakdown Voltage Emitter-Collector Breakdown	30 V 5 V		WIRELESS POS ENABLES MONI	HONEYWELL'S XYR6000 WIRELESS POSITION SENSOR ENABLES MONITORING IN HAZARDOUS AREAS AND	
Wireless Switches Offer Unlimited Benefit	Voltage Collector-Emitter Saturation Voltage	0.4 V		HAZARDOUS AF REMOTE LOCAT		
Basic Switches Are Not Created	Comment	The radiation source is a tungsten lamp operat 2870°K.	ting at a color temperature of			
Equal Applying Precision Switches Sensors for Medical Devices	Availability	Global			ICRO SWIT(iniversary s	
New Ways to Measure Torque						

Need help?

Click here to contact us

Choosing Safety Switches Specifying Hour Meters

Terms & Conditions | Privacy Statement | Site Map

1/17/2011