



Representative photograph, actual product appearance may vary.

Due to regional agency approval requirements, some products may not be available in your area. Please contact your regional Honeywell office regarding your product of choice.

UM50E70F01

UM Series Subminiature Basic Switch, Single Pole Double Throw (SPDT), 250 Vac, 5 A, Roller Lever Actuator, Quick Connect Termination

Features

- Choice of low energy or power duty electrical ratings (gold or silver contacts)
- Form C single-pole double-throw (SPDT) circuitry
- Rated to 10 A
- Choice of actuation, termination and operating characteristics

Typical Applications

- Appliances
- Vending machines
- Timing devices
- Office equipment
- Computer/business equipment
- Test instruments
- Medical/dental equipment
- Communications equipment
- HVAC equipment
- Manually operated devices
- Valves

Description

UM Series Subminiature Basic Switches are used for simple or precision ON/OFF application needs. The UM Series Switches are slightly larger than the UX Series Switches. These switches combine small size and light weight with ample electrical capacity, low cost and long life.



UM50E70F01

UM Series Subminiature Basic Switch, Single Pole Double Throw (SPDT), 250 Vac, 5 A, Roller Lever Actuator, Quick Connect Termination

Product Specifications	
Switch Type	Subminiature 12,7 mm H x 6,35 mm W x 20,3 mm L [0.5 in H x 0.25 in W x 0.8 in L]
Sealed	No
Ampere Rating	5 A
Circuitry	Single Pole Double Throw (SPDT)
Actuator	Roller Lever

Termination	Quick Connect
Operating Temperature Range	-25 °C to 82 °C [-13 °F to 180 °F]
Voltage	250 Vac
Approvals	CE, CSA, SEMKO, UL, VDE
Actuator Length	5,15 mm [0.203 in]
Contact Type	Silver
Operating Force (O.F.)	0,58 N [2.1 oz] max.
Release Force (R.F.)	0,04 N [0.141 oz] min.
Pretravel (P.T.)	2,5 mm [0.098 in] max.
Overtravel (O.T.)	0,8 mm [0.031 in] min.
Differential Travel (D.T.)	0,50 mm [0.020 in] max.
Operating Position (O.P.)	14,50 mm ± 0,8 mm [0.571 in ± 0.031 in]
Housing Material	Thermoplastic
CE mark	61058-1
UL File #	E12252
CSA File #	LR23413M167
Agency Approvals and Standards	1054
Mounting Screw Size	2,3 mm [0.09 in]
Mounting Centers	9,65 mm [0.38 in]
Maximum Tightening Torque	0,29 N m [2.6 in lb]
Weight	0,2 g [0.007 oz]
Package Height	10,9 mm [0.43 in]
Package Width	6,35 mm [0.25 in]
Package Length	19,8 mm [0.78 in]
Availability	Global
UNSPSC Code	30211905
UNSPSC Commodity	30211905 Snap switches
Series Name	UM Series



UM50E70F01

UM Series Subminiature Basic Switch, Single Pole Double Throw (SPDT), 250 Vac, 5 A, Roller Lever Actuator, Quick Connect Termination

UM50E70F01

⚠ WARNING

Failure to comply with these instructions could result in death or serious injury.

! WARNING

Failure to comply with these instructions could result in death or serious injury.

© *Copyright Honeywell Inc.1998-2004 All rights reserved.*