

## Fast switching diode chip in EMCON 3 -Technology

### FEATURES:


- 600V EMCON 3 technology 70  $\mu\text{m}$  chip
- soft, fast switching
- low reverse recovery charge
- small temperature coefficient

### This chip is used for:

- power module
- discrete components

### Applications:

- drives
- white goods
- resonant applications



Chip Type	$V_R$	$I_F$	Die Size	Package
SIDC02D60C6	600V	6A	1.4 x 1.65 mm <sup>2</sup>	sawn on foil

### MECHANICAL PARAMETER:

Raster size	1.4 x 1.65	mm <sup>2</sup>
Area total / active	2.31 / 1.31	
Anode pad size	0.98 x 1.23	
Thickness	70	$\mu\text{m}$
Wafer size	150	mm
Flat position	180	deg
Max. possible chips per wafer	6468 pcs	
Passivation frontside	Photoimide	
Anode metallization	3200 nm AlSiCu	
Cathode metallization	Ni Ag –system suitable for epoxy and soft solder die bonding	
Die bond	electrically conductive glue or solder	
Wire bond	Al, $\leq 500\mu\text{m}$	
Reject ink dot size	$\varnothing$ 0.65mm; max 1.2mm	
Recommended storage environment	store in original container, in dry nitrogen, < 6 month at an ambient temperature of 23°C	

## Maximum Ratings

Parameter	Symbol	Condition	Value	Unit
Repetitive peak reverse voltage	$V_{RRM}$		600	V
Continuous forward current limited by $T_{jmax}$	$I_F$		1)	A
Maximum repetitive forward current limited by $T_{jmax}$	$I_{FRM}$		12	
Operating junction and storage temperature	$T_j, T_{stg}$		-40...+175	°C

1) depending on thermal properties of assembly

Static Electrical Characteristics (**tested on chip**),  $T_j=25\text{ °C}$ , unless otherwise specified


Parameter	Symbol	Conditions		Value			Unit
				min.	Typ.	max.	
Reverse leakage current	$I_R$	$V_R=600V$	$T_j=25\text{ °C}$			27	µA
Cathode-Anode breakdown Voltage	$V_{Br}$	$I_R=0.25mA$	$T_j=25\text{ °C}$	600			V
Forward voltage drop	$V_F$	$I_F=6A$	$T_j=25\text{ °C}$	1.25	1.6	1.95	V

Dynamic Electrical Characteristics (verified by design/characterization), inductive load

Parameter	Symbol	Conditions		Value <sup>2)</sup>			Unit
				min.	Typ.	max.	
Peak reverse recovery current	$I_{RM}$	$I_F=6A$ $di/dt=800A/ms$ $V_R=300V$ $V_{GE}=-15V$	$T_j = 25\text{ °C}$ $T_j = 125\text{ °C}$ $T_j = 150\text{ °C}$		10.5 11.5 12.0		A
Recovered charge	$Q_r$	$I_F=6A$ $di/dt=800A/ms$ $V_R=300V$ $V_{GE}=-15V$	$T_j = 25\text{ °C}$ $T_j = 125\text{ °C}$ $T_j = 150\text{ °C}$		0.35 0.60 0.70		µC
Reverse recovery energy	$E_{rec}$	$I_F=6A$ $di/dt=800A/ms$ $V_R=300V$ $V_{GE}=-15V$	$T_j = 25\text{ °C}$ $T_j = 125\text{ °C}$ $T_j = 150\text{ °C}$		0.065 0.12 0.16		mJ

<sup>2)</sup> values also influenced by parasitic L- and C- in measurement and package.

## CHIP DRAWING:





# SIDC02D60C6

## FURTHER ELECTRICAL CHARACTERISTICS:

This chip data sheet refers to the device data sheet	FS6R06VE3	
--	-----------	--

## Description:

AQL 0,65 for visual inspection according to failure catalog

Electrostatic Discharge Sensitive Device according to MIL-STD 883

Test-Normen Villach/Prüffeld

**Published by**  
**Infineon Technologies AG**  
**81726 München, Germany**  
**© Infineon Technologies AG 2006.**  
**All Rights Reserved.**

## Attention please!

The information herein is given to describe certain components and shall not be considered as warranted characteristics.

Terms of delivery and rights to technical change reserved.

We hereby disclaim any and all warranties, including but not limited to warranties of non-infringement, regarding circuits, descriptions and charts stated herein.

Infineon Technologies is an approved CECC manufacturer.

## Information

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office in Germany or our Infineon Technologies Representatives world-wide (see address list).

## Warnings

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies Office.

Infineon Technologies components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body, or to support and / or maintain and sustain and / or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.