



English | 简体中文 | 日本語

Search Entire Site [GO](#)

[Contact IDT](#) | [Investors](#) | [Press](#)

[About IDT](#)

[Products](#)

[Applications](#)

[Support](#)

[myIDT](#)

[Document Search](#) | [Package Search](#) | [Parametric Search](#) | [Cross Reference Search](#) | [Green & RoHS](#) | [Calculators](#) | [Thermal Data](#) | [Reliability & Quality](#) | [Military](#)

[Home](#) > [Products](#) > > [ZTM202C](#) > [ZTM202C-A](#)

[Add to myIDT \[?\]](#)

You may also like...

ZTM202C-A

Category:

Generic Part:

Market Group:

Description:

[ZTM202C](#)

SSP

SWITCH FABRIC

**Time is
money**

Parameters

Package	FCBGA 241 (BL1241)
Speed	NA
Temperature	C
Voltage	5.0 V
Status	Active
Sample	Yes
Minimum Order Quantity	1
Factory Order Increment	1

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

No documents available for this part at this time.

Package

Description	FLIP CHIP BGA 40.0 X 40.0 MM X 1.0 MM PI
Class	PLASTIC
Moisture Sensitivity Level (MSL)	4
Category	Standard
Moisture Exposure Floor Life	72 hrs. @ <30°C/60%RH
Peak Reflow Temperature	225°C
Rebake Conditions	48 hrs.@125°C
Length	40.0
Mark	\
Width	40.0
Pitch	1.0
Thickness	2.82
Status	Active

[Home](#) | [Site Map](#) | [Legal](#) | [Careers](#) | [Contact Us](#) | [Quality](#) | [RSS](#) What is this?

Use of this website signifies your agreement to the [acceptable use](#) and [privacy policy](#). Copyright © 1997-2008 Integrated Device Technology, Inc. [All Rights Reserved](#).