Print Page

Device Information

ISL95835

- 3+1 and 1+1 Voltage Regulator for IMVP-7/VR12™ CPUs
- Features Description
- iSim Design Simulation Tools And Support
- Technical Documentation Pricing / Samples
- Related Devices

Datasheet



ISL95835

The ISL95835, ISL95837 datasheet is restricted to a very limited number of customers. To request a datasheet please email Jia Wei at jwei@intersil.com

V _{IN} (min) (V)	4.5
V _{IN} (max) (V)	5.5
V _{OUT} (min) (V)	0
V _{OUT} (max) (V)	1.52
I _{OUT} (max) (A)	90
V _{BIAS} (V)	5
Applications	VR12/IMVP7
Max # of outputs	2
Max # of phases	3
Droop	Y
Integrated MOSFET Driver	Y

Product Information

Key Features

Serial Data Bus **Dual Outputs:** Configurable 3-, 2- or 1-phase for the 1st Output using 2 integrated Gate Drivers 1-phase for the 2nd Output using an Integrated Gate Driver 0.5% System Accuracy Over-Temperature Supports Multiple Current Sensing Methods Lossless Inductor DCR Current Sensing Precision Resistor Current Sensing Differential Remote Voltage Sensing Programmable VBOOT Voltage at Start-up Resistor Programmable I_{MAX} , T_{MAX} for Both Outputs Adaptive Body Diode Conduction Time Reduction

Description

Compliant with IMVP-7/VR12TM, the ISL95835 provides a complete solution for microprocessor and graphic processor core power supply. It provides two Voltage Regulators (VRs) with three integrated gate drivers. The first VR can be configured as

3-, 2- or 1-phase VR while the second output is 1-phase VR, providing maximum flexibility. The two VRs share the serial control bus to communicate with the CPU and achieve lower cost and smaller board area compared with the two-chip approach.

Based on Intersil's Robust Ripple Regulator (R3) technology™, the PWM modulator compared to traditional modulators, has faster transient settling time, variable switching frequency during load transients and has improved light load efficiency with it's ability to automatically change switching frequency.

The ISL95835 has several other key features. Both outputs support DCR current sensing with single NTC thermistor for DCR temperature compensation or accurate resistor current sensing. Both outputs come with remote voltage sense, programmable V_{BOOT} voltage, programmable I_{MAX}, T_{MAX}, adjustable switching frequency, OC protection and separate Power-Good.

The ISL95837 can be considered as ISL95835 dedicated for 1+1 application. VR1 and VR2 are both 1-phase VR.

Pricing / Packaging / Samples / Ordering

iBuy direct from Intersil Check distributor inventory		ct - out of stock 🧾	Request samples				
Part No.	Design-In Status	Temp.	Package	MSL	Price US \$	ß	
ISL95835HRZ	Active	Hi-Temp Comm	40 Ld QFN	3			0
ISL95835HRZ-T	Active	Hi-Temp Comm	40 Ld QFN T+R	3			0
ISL95835IRZ	Active	Ind	40 Ld QFN	3			00
ISL95835IRZ-T	Active	Ind	40 Ld QFN T+R	3			0

The price listed is the manufacturer's suggested retail price for quantities of 1K units. However, prices in today's market are fluid and may change without notice.

MSL = Moisture Sensitivity Level - per IPC/JEDEC J-STD-020

SMD = Standard Microcircuit Drawing

Technical Documentation

Datasheet(s):

The ISL95835, ISL95837 datasheet is restricted to a very limited number of customers. To request a datasheet please email Jia Wei at jwei@intersil.com

Tools And Support

iSim Design Simulation

No Models Available

Applications

IMVP-7/VR12 Compliant Computers

Related Devices

ISL6353	Multiphase PWM Regulator for VR12 DDR Memory Systems
ISL6363	Multiphase PWM Regulator for VR12™ Desktop CPUs
ISL6364	Dual 4-Phase + 1-Phase PWM Controller for VR12/IMVP7 Applications
ISL6364C	Dual 4-Phase + 1-Phase PWM Controller for VR12 Desktop Applications
ISL6366	Dual 6-Phase + 1-Phase PWM Controller for VR12/IMVP7 Applications
ISL95831	3+1 Voltage Regulator for IMVP-7/VR12 CPUs
ISL95837	3+1 and 1+1 Voltage Regulator for IMVP-7/VR12™ CPUs

About Us | Careers | Contact Us | Investors | Legal | Privacy | Site Map | Subscribe | Intranet



PT Parametric Table

©2003-2011. Intersil Americas Inc. All rights reserved.