



Datasheet for part number DAJK15S41AWN

| |
|---|
| Our Catalog Part Number: DAJK15S4-1AWN |
| Our Global Manufacturing Part Number: 121560-0424 |
| Brand: Cannon Product Category: D Sub Product Line: D Sub Series: D*JK / D*JT |

| Product Datasheet | |
|---------------------------------|---|
| General | Filter D |
| Filter Type | tublar ceramic filter |
| Filter Capacity | 1000 pF |
| Wire Gauge Range AWG | AWG 20-28 |
| Mating Cycles | 200 |
| Dielectric Withstanding Voltage | 250 VAC at sea level |
| Current Rating Signal Contacts | 5 A max. |
| Contact Resistance | 10 milli Ohm max |
| Operating Temperature | -55°/+125° |
| Salt Spray Test | 20 hours |
| Shell Material | steel |
| Shell Finish | tin |
| Insulator Material | glass filled Thermoplastic, type PCT UL 94V-0 |
| Insulator Color | white |
| Number of Contacts | 15 contacts size 20 |
| Gender | Socket |
| Contact Type | turned |
| Contact Material | copper alloy |
| Contact Finish | gold flash (Performance Class 2) |
| Contact Termination | Right angled solder |
| Mounting Methode | plastic bracket with grounding bracket and captive nut 4-40 |
| Row Spacing | 2,54 mm |