



Datasheet for part number DAMAM15PF225F0

|  |  |
|--|--|
| Our Catalog Part Number: DAMAM-15P-F225-F0 |  |
| Brand: Cannon                              | Product Category: D Sub   Product Line: D Sub   Series: D*MA |

| Product Datasheet               |  |
|---------------------------------|--|
| General                         | D*M High reliable D-Sub Connectors with crimp termination        |
| Wire Gauge Range AWG            | Standard: AWG 20-28. High Density: AWG 22-28                     |
| Mating Cycles                   | 500  |
| Contact Arrangement             | Standard: 15 contacts size 20. High Density: 15 contacts size 22 |
| Dielectric Withstanding Voltage | 1000 VAC at sea level  |
| Current Rating                  | 7.5 A max  |
| Contact Resistance              | 10 milli Ohm max   |
| Operating Temperature           | -55°/+150°   |
| Salt Spray Test                 | 48 hours   |
| Shell Material                  | Passivated stainless steel                                       |
| Shell Finish                    | Stainless steel shell  |
| Insulator Material              | Thermoplastic, type PCT UL 94V-0                                 |
| Insulator Color                 | black  |
| Gender                          | Pin  |
| Contacts                        | delivery without contacts, please order separately               |
| Contact Type                    | Crimp  |
| Contact Material                | copper alloy   |
| Contact Finish                  | gold over nickel (Performance Class 2)                           |
| Hardware                        | .120" (3,05mm) Through Hole                                      |