

HTZ110A Series

$$I_{F(AV)} = 3.5 \text{ A}$$


$$V_{RRM} = 25000 \text{ V}$$

High Voltage Diode Rectifier Module

LARONTROL
Electronic Devices

Type Number	Repetitive Peak	Minimum Avalanche Voltage $V_{(BR)R}$
HTZ110A25K	25000	27200
HTZ110A22K	22000	24000
HTZ110A19K	19000	20800
HTZ110A16K	16000	17600

CIRCUIT DIAGRAM





CURRENT RATINGS - AIR COOLED

$I_{F(AV)}$ Mean forward current

I_F Continuous (direct) forward current

$R_{th(j-a)}$ Thermal resistance junction to ambient

Half wave resistive load $T_{amb} = 35^\circ\text{C}$

$T_{amb} = 35^\circ\text{C}$

3.5 A

4.3 A

2.3 $^\circ\text{C/W}$

CURRENT RATINGS - OIL COOLED

$I_{F(AV)}$ Mean forward current

I_T Continuous (direct) forward current

$R_{th(j-o)}$ Thermal resistance junction to oil

Half wave resistive load $T_{oil} = 60^\circ\text{C}$

$T_{oil} = 60^\circ\text{C}$

5.7 A

7.0 A

0.93 $^\circ\text{C/W}$

SURGE RATINGS

I^2t I^2t for fusing

I_{FSM} Surge (non-repetitive) forward current

10 ms half sine $T_{vj} = 150^\circ\text{C}$

$T_{vj} = 150^\circ\text{C}$

200 A^2sec

200 A

TEMPERATURE AND FREQUENCY RATINGS

T_{vj} Virtual junction temperature

Forward (conducting)

180 $^\circ\text{C}$

Reverse (blocking)

180 $^\circ\text{C}$

T_{stg} Storage temperature range

-40 to 100 $^\circ\text{C}$

f Frequency range

20 to 400 Hz

CHARACTERISTICS $T_{case} = 25^\circ\text{C}$ unless otherwise stated

V_{FM} Forward voltage

At 12 Amps peak

max 18.3 V

I_{RM} Peak reverse current


At V_{RRM} ; $T_{case} = 150^\circ\text{C}$

max 0.5 mA

Dimensioned Outlines

Dimensions shown are maximum in mm

Weight typ.: 1,55 Kg



IXYS reserves the right to change limits, test conditions and dimensions.

ZA

Issue 1 June 1998

Distributed by

USA
3540 Bassett Street
Santa Clara, CA 95054
Phone: (408) 982-0700
FAX: (408) 496-0670

EUROPE
IXYS Semiconductor GmbH
Lampertheim Germany
Phone: +49.6206.503.0
Fax: +49.6206.503.627

IXYS
www.IXYS.net

HTZ110A Series

$$I_{F(AV)} = 3.5 \text{ A}$$

$$V_{RRM} = 25000 \text{ V}$$

High Voltage Diode Rectifier Module

LARONTROL
Electronic Devices

